


# Class H(K), J and R modular ferrule fuse blocks



## Product description:

HM Class H(K), JM Class J and RM Class R modular ferrule fuse blocks for fuses up to 60 amps.

The new Bussmann™ series fuse blocks contain multiple features that increase versatility, reduce labor and enhance safety for any panel or electrical system design.

## Features and benefits:

- Available in 1-, 2-, and 3-pole configurations to meet stocking requirements.
- To reduce inventory, assembly time and labor, modular single-pole blocks snap-together for tool-less assembly of multiple poles at point of use.
- DIN-Rail and panel mount versatility allows one product to be used for multiple applications with lower inventory cost.
- Save panel space with the smallest width dimension on the market.
- Standard clip reinforcing springs improve temperature rise performance while maintaining reliable surface contact between the fuse ferrule and clip over the block's service life.
- Optional see-through, IP20 finger-safe covers enhance safety with lock-out/tag-out capability.
- Optional open fuse indication on covers speeds troubleshooting.
- Easy circuit identification with available universal marker labels for blocks and covers.

## Specifications

### Ratings:

- Volts Class H 250V, 600V  
Class J 600V  
Class R 250V, 600V
- Amps up to 60A
- Withstand Class J and R 200kA RMS Sym  
Class H(K) 10kA RMS Sym

### Agency information:

#### Blocks:

- UL® Listed E14853 - IZLT
- CSA® Certified 47235-6225-01
- CE
- RoHS Compliant
- Conflict mineral free
- REACH declaration available upon request

#### Covers:

- UL Listed E58836 - JDVS
- CSA Certified 47235-6225-01
- RoHS Compliant
- REACH declaration available upon request

### Poles:

- 1-, 2-, 3-pole units factory assembled
- Single-pole units snap together to create desired number of poles

### Flammability ratings:

- Blocks — UL 94V0, self-extinguishing
- Covers — UL 94HB, self-extinguishing

### Operating and storage temperature range:

- Blocks -40°C to +120°C
- Non-Indicating covers -40°C to +120°C
- Indicating covers -20°C to +90°C\*

\* Indication requires minimum 90Vac/dc and closed circuit to illuminate.

### Materials:

- Base — Thermoplastic
- Terminals — Tin-plated copper brass
- Covers — Thermoplastic

### Recommended Bussmann series fuses:

#### Class H(K)

- Basic protection general purpose 250V NON, data sheet No. 1030
- Basic protection general purpose 600V NOS, data sheet No. 1030

#### Class J

- Ultimate protection Low-Peak™ LPJ time-delay fuses, data sheet No. 1006
- Advanced protection Limitron™ JKS fast-acting fuses, data sheet No. 1026

#### Class R

- Ultimate protection Low-Peak LPN 250V time-delay, data sheet No. 1003
- Ultimate protection Low-Peak LPS 600V time-delay, data sheet No. 1001
- Advanced protection Limitron KTN-R 250V fast-acting, data sheet No. 1043
- Advanced protection Limitron KTS-R 600V fast-acting, data sheet No. 1044
- Advanced protection energy efficient Fusetron™ FRN 250V time-delay, data sheet No. 1019
- Advanced protection energy efficient Fusetron FRS, 600V time-delay, data sheet No. 1017

### Recommended Bussmann series DIN-Rail end stops:

- Part No. BRKT-ND
- Part No. BRKT-NDSCREW2

### Marker labels:

- Use Bussmann series part number TM26CB

Table 1. Terminals, conductors and torque values

| Terminal type         | AWG type/range       | Torque |             |
|-----------------------|----------------------|--------|-------------|
|                       |                      | AWG    | Lb-in (N•m) |
| Box Lug ("CR" Option) | 75°C Cu 2-14, AL 2-8 | 2-3;   | 50 (5.6)    |
|                       |                      | 4-6;   | 45 (5.1)    |
|                       |                      | 8;     | 40 (4.5)    |
|                       |                      | 10-14; | 35 (4.0)    |
| All other terminals*  | 75/90°C Cu 10-18     | 10-18; | 20 (2.3)    |

\* 3/16" Quick Connect terminal maximum ampacity dependent on female spade connector and wire ratings.

Table 2. Class H fuse block catalog numbers

| Box lug     | Terminal type          |                           |                | Volts | Fuse amp range | Poles |
|-------------|------------------------|---------------------------|----------------|-------|----------------|-------|
|             | #10-32 Phil-slot screw | Screw with quick-connect* | Pressure plate |       |                |       |
| HM25030-1CR | HM25030-1SR            | HM25030-1QR               | HM25030-1PR    | 250   | 1/2 to 30      | 1     |
| HM25030-2CR | HM25030-2SR            | HM25030-2QR               | HM25030-2PR    |       |                | 2     |
| HM25030-3CR | HM25030-3SR            | HM25030-3QR               | HM25030-3PR    |       |                | 3     |
| HM25060-1CR | —                      | —                         | —              |       | 31 to 60       | 1     |
| HM25060-2CR | —                      | —                         | —              |       |                | 2     |
| HM25060-3CR | —                      | —                         | —              |       |                | 3     |
| HM60030-1CR | HM60030-1SR            | —                         | HM60030-1PR    | 600   | 1/2 to 30      | 1     |
| HM60030-2CR | HM60030-2SR            | —                         | HM60030-2PR    |       |                | 2     |
| HM60030-3CR | HM60030-3SR            | —                         | HM60030-3PR    |       |                | 3     |
| HM60060-1CR | —                      | —                         | —              |       | 31 to 60       | 1     |
| HM60060-2CR | —                      | —                         | —              |       |                | 2     |
| HM60060-3CR | —                      | —                         | —              |       |                | 3     |

\* 3/16" Quick Connect terminal maximum ampacity dependent on female spade connector and wire ratings.

Table 3. Class H block covers

| Fuse block series | Volts | Amp range | Catalog numbers |                |
|-------------------|-------|-----------|-----------------|----------------|
|                   |       |           | Indicating      | Non-indicating |
| HM25030-#XX       | 250   | 1/2 to 30 | CVRI-RH-25030   | CVR-RH-25030   |
| HM25060-#XX       |       | 31 to 60  | CVRI-RH-25060   | CVR-RH-25060   |
| HM60030-#XX       | 600   | 1/2 to 30 | CVRI-RH-60030   | CVR-RH-60030   |
| HM60060-#XX       |       | 31 to 60  | CVRI-RH-60060   | CVR-RH-60060   |

# = number of poles

XX = terminal type



Table 4. Class R fuse block catalog numbers

| Box lug     | Terminal type          |                          |                | Volts | Fuse amp range | Poles |
|-------------|------------------------|--------------------------|----------------|-------|----------------|-------|
|             | #10-32 Phil-slot screw | Screw with quick-connect | Pressure plate |       |                |       |
| RM25030-1CR | RM25030-1SR            | RM25030-1QR              | RM25030-1PR    | 250   | 1/2 to 30      | 1     |
| RM25030-2CR | RM25030-2SR            | RM25030-2QR              | RM25030-2PR    |       |                | 2     |
| RM25030-3CR | RM25030-3SR            | RM25030-3QR              | RM25030-3PR    |       |                | 3     |
| RM25060-1CR | —                      | —                        | —              |       | 31 to 60       | 1     |
| RM25060-2CR | —                      | —                        | —              |       |                | 2     |
| RM25060-3CR | —                      | —                        | —              |       |                | 3     |
| RM60030-1CR | RM60030-1SR            | —                        | RM60030-1PR    | 600   | 1/2 to 30      | 1     |
| RM60030-2CR | RM60030-2SR            | —                        | RM60030-2PR    |       |                | 2     |
| RM60030-3CR | RM60030-3SR            | —                        | RM60030-3PR    |       |                | 3     |
| RM60060-1CR | —                      | —                        | —              |       | 31 to 60       | 1     |
| RM60060-2CR | —                      | —                        | —              |       |                | 2     |
| RM60060-3CR | —                      | —                        | —              |       |                | 3     |

\* 3/16" Quick Connect terminal maximum ampacity dependent on female spade connector and wire ratings.

Table 5. Class R block covers

| Fuse block series | Volts | Amp range | Catalog numbers |                |
|-------------------|-------|-----------|-----------------|----------------|
|                   |       |           | Indicating      | Non-indicating |
| RM25030-#XX       | 250   | 1/2 to 30 | CVRI-RH-25030   | CVR-RH-25030   |
| RM25060-#XX       |       | 31 to 60  | CVRI-RH-25060   | CVR-RH-25060   |
| RM60030-#XX       | 600   | 1/2 to 30 | CVRI-RH-60030   | CVR-RH-60030   |
| RM60060-#XX       |       | 31 to 60  | CVRI-RH-60060   | CVR-RH-60060   |


# = number of poles

XX = terminal type





# Dimensions - mm (in):

## Class H(K) and R 250V - 30A block




## Class H(K) and R 250V - 60A block



**Dimensions - mm (in):****Class H(K) and R 600V - 30A block**

With cover.  
See tables 3 and 5 for available covers.

**Class H(K) and R 600V - 60A block**

With cover.  
See tables 3 and 5 for available covers.

Table 6. Class J fuse block catalog numbers


| Terminal type |                        |                | Volts | Fuse amp range | Poles |
|---------------|------------------------|----------------|-------|----------------|-------|
| Box lug       | #10-32 Phil-slot screw | Pressure plate |       |                |       |
| JM60030-1CR   | JM60030-1SR            | JM60030-1PR    | 600   | 1/2 to 30      | 1     |
| JM60030-2CR   | JM60030-2SR            | JM60030-2PR    |       |                | 2     |
| JM60030-3CR   | JM60030-3SR            | JM60030-3PR    |       |                | 3     |
| JM60060-1CR   | —                      | —              | 600   | 31 to 60       | 1     |
| JM60060-2CR   | —                      | —              |       |                | 2     |
| JM60060-3CR   | —                      | —              |       |                | 3     |

Table 7. Class J block covers

| Fuse block series | Volts | Amp range | Catalog numbers |                |
|-------------------|-------|-----------|-----------------|----------------|
|                   |       |           | Indicating      | Non-indicating |
| JM60030-#XX       | 600   | 1/2 to 30 | CVRI-J-60030    | CVR-J-60030    |
| JM60060-#XX       |       | 31 to 60  | CVRI-J-60060    | CVR-J-60060    |


# = number of poles  
XX = terminal type



**Dimensions - mm (in):****Class J - 30A block**

With cover.

See table 7 for available covers.


**Class J - 60A block**

With cover.


See table 7 for available covers.

### Installing/removing covers


Closing cover: Position cover over block and push straight down until it snaps/clicks into place.




Opening cover: Using both outside handles, pull straight up.



### Installing blocks on DIN-Rail



Place one edge of DIN-Rail in fuse block base, then rotate block down until it clicks into place.



The only controlled copy of this data sheet is the electronic read-only version located on the Eaton network drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

**Eaton**  
1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
Eaton.com

Bussmann Division  
114 Old State Road  
Ellisville, MO 63021  
United States  
Eaton.com/bussmannseries

© 2017 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. 10289 - BU-SB14607  
March 2017

Eato, Bussmann, Fusetron, Limitron and Low-Peak are valuable trademarks of Eaton in the US and other countries. You are not permitted to use the Eaton trademarks without prior written consent of Eaton.

CSA is a registered trademark of the Canadian Standards Group.  
UL is a registered trademark of Underwriters Laboratories, Inc.

For Eaton's Bussmann series product information, call 1-855-287-7626 or visit: [Eaton.com/bussmannseries](http://Eaton.com/bussmannseries)

Follow us on social media to get the latest product and support information.

