




P.C.B LAYOUT

(N= Number of poles)

| DIM   |                | TOL   |        |         |
|-------|----------------|-------|--------|---------|
|       |                | 2P-5P | 6P-10P | 11P-16P |
| Dim L | (N-1)×7.5+18   | ±0.15 | ±0.25  | ±0.35   |
| Dim A | (N-1)×7.5+5.52 | ±0.15 | ±0.25  | ±0.35   |
| Dim B | (N-1)×7.5      | ±0.15 | ±0.25  | ±0.35   |
| Dim C | (N-1)×7.5      | ±0.15 | ±0.25  | ±0.35   |
| Dim D | (N-1)×7.5+12.2 | ±0.15 | ±0.25  | ±0.35   |

| SIGN | DATE     | DESCRIPTION                                                 | APPROVER |
|------|----------|-------------------------------------------------------------|----------|
| △    | 01/15'10 | The design is changed                                       | Jacke    |
| △    | 01/15'10 | The design is changed from the round hole to hexagonal hole | Jacke    |
| △    | 01/15'10 | Add cULus standard                                          | Jacke    |
| △    | 03/31'10 | Add the 2p mark                                             | Jacke    |
| △    | 04/28'12 | Flange Nut is changed                                       | Guoxue   |
| △    | 04/28'12 | Add the cutaway view                                        | Guoxue   |
| △    | 04/28'12 | The dimensions are added                                    | Guoxue   |

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

### Materials

- Item a Terminal body:Thermoplastic (UL94V-0)  
Item b Terminal Cover:Thermoplastic (UL94V-0)  
Item c Female contact :PhBz(CuSn), Tin plated  
Item d With flange Nut : Brass M 2.5

### Electrical

- Voltage rating: 300VAC
- Current rating: 10A
- Withstanding Voltage: 1.6kv
- Operating temperature: -40°C to +115°C
- Soldering temperature: 250°C±10°C/5 Sec
- Safety Approval: cULus

- Critical dimension:

V7 xx A 2 x 1 xxxx G

No. OF POLES  
02 2 POLES  
03 3 POLES  
...  
16 16 POLES

### Color

- 0 Black (RAL9005)  
2 Red (RAL3001/D)  
3 Orange(RAL2011/P)  
4 Yellow(RAL1018/A)  
5 Green(RAL6018/T)  
6 Blue (RAL5015/A)  
8 Grey(RAL7035/D)

G RoHS compliant  
(lead<4%)  
In copper Alloy

0000: "@" Logo (Standard)  
000A: "ANYTEK" Mark  
Any special item by  
customer request.  
please contact sales  
department.

# ANYTEK

## INSPECTION COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

|          |               |                                       |                      |                                                                                       |            |           |
|----------|---------------|---------------------------------------|----------------------|---------------------------------------------------------------------------------------|------------|-----------|
| TITLE    |               | V7 7.5 Series Right-angle (2P~16P)W/F |                      |                                                                                       |            |           |
| PART NO. | V7xxA2x1xxxxG |                                       |                      | DWG NO.                                                                               | 8V70404    |           |
| APPROVED | CHECKED       | DESIGNED                              | DRAWN                | CUST NO.                                                                              |            |           |
|          |               | Guoxue<br>2012.04.28                  | Guoxue<br>2012.04.28 |  | UNIT: mm   | X. ±0.5   |
|          |               |                                       |                      |                                                                                       | SCALE: 1/4 | X.X ±0.3  |
|          |               |                                       |                      |                                                                                       | REV.: E    | X.XX ±0.1 |
|          |               |                                       |                      | SHEET: 01/01                                                                          |            | X° ±1°    |