

Panel feed-through - Q 1,5/4FL/16-16KU-ESA GY - 1418850

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



QUICKON panel feed-through, for external panel mounting with manual solder/slip-on plug-in connection, 4.8 x 0.8 mm, 4-pos.


As illustrated, but with gray design

Your advantages

- ✓ Robust throughout: housing with IP65/IP67 protection for a wide range of applications

RoHS

Key Commercial Data

Packing unit	10 pc
Minimum order quantity	500 pc
GTIN	 4 055626 152257
GTIN	4055626152257

Technical data

General

Number of positions	4
---------------------	---

Electrical characteristics

Nominal current I_N	17.5 A (15 A with slip-on sleeve 2.5 mm ² ; 12 A with slip-on sleeve 1.5 mm ² .)
-----------------------	--

Mechanical characteristics

Impact category	4
-----------------	---

Material data

Flammability rating according to UL 94	V0
Overvoltage category	III
Degree of pollution	3

Standards and Regulations

Panel feed-through - Q 1,5/4FL/16-16KU-ESA GY - 1418850

Technical data

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		RU C- DE.A*30.B.01102
-----	---	--------------------------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>