

## Panel feed-through - Q 1,5/4FL/16-16KU-ESA GY - 1418850

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



QUICKON panel feed-through, for external panel mounting with manual solder/slip-on plug-in connection, 4.8 x 0.8 mm, 4-pos.


As illustrated, but with gray design

### Your advantages

- ✓ Robust throughout: housing with IP65/IP67 protection for a wide range of applications

RoHS

### Key Commercial Data

|                        |   |
|------------------------|---|
| Packing unit           | 10 pc   |
| Minimum order quantity | 500 pc  |
| GTIN                   | <br>4 055626 152257 |
| GTIN                   | 4055626152257   |

### Technical data

#### General

|                     |   |
|---------------------|---|
| Number of positions | 4 |
|---------------------|---|

#### Electrical characteristics

|                       |  |
|-----------------------|--|
| Nominal current $I_N$ | 17.5 A (15 A with slip-on sleeve 2.5 mm <sup>2</sup> ; 12 A with slip-on sleeve 1.5 mm <sup>2</sup> .) |
|-----------------------|--|

#### Mechanical characteristics

|                 |   |
|-----------------|---|
| Impact category | 4 |
|-----------------|---|

#### Material data

|  |     |
|--|-----|
| Flammability rating according to UL 94 | V0  |
| Overvoltage category                   | III |
| Degree of pollution                    | 3   |

### Standards and Regulations

## Panel feed-through - Q 1,5/4FL/16-16KU-ESA GY - 1418850

### Technical data

#### Standards and Regulations

|  |    |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

### Approvals

#### Approvals

#### Approvals

EAC

#### Ex Approvals

#### Approval details

|     |   |                          |
|-----|---|--------------------------|
| EAC |  | RU C-<br>DE.A*30.B.01102 |
|-----|---|--------------------------|

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>