







0955 329 3821 741	1	M3	Black insulator	Reel Packaging: 140 connectors (See details on page2/2)					
0955 329 3822 741	1	4-40 UNC							
0955 329 6821 741	2	M3							
0955 329 6822 741	2	4-40 UNC							
0955 329 7821 741	3	M3							
0955 329 7822 741	3	4-40 UNC							
Part number	PL	Screw lock	Index designation						
 All Dimensions in mm Original Size DIN A 3			Techn. Character.		Free size tolerances				
				Dat.	Name	Scale 2 : 1	D-Sub SMT, 25 poles Male, Straight with screw locks and ground pads		
			Detail.	25-Oct-11	Johnson.S				
			Insp.	17-Nov-11	Steven.W				
			Stand.	17-Nov-11	Steven.W				
EC04070	17-Nov-11	Johnson.S	Zhuhai HARTING Limited					TB 09 55 329 x82x	Page 1 / 2
Mod.	Dat.	Name				Sub.			


PCB layout, component side



Detail A



Direction of unreeling →



See TB 09 55 329 x82x folio 1/2 for connector dimensions and PCB layout

Packaging in accordance with EIA 481-2.

0955 329 3821 741	1	M3	Black insulator	Reel Packaging: 140 connectors
0955 329 3822 741	1	4-40 UNC		
0955 329 6821 741	2	M3		
0955 329 6822 741	2	4-40 UNC		
0955 329 7821 741	3	M3		
0955 329 7822 741	3	4-40 UNC		
Part number	PL	Screw lock	Index designation	

 All Dimensions in mm Original Size DIN A 3			Techn. Character.			Free size tolerances			
				Dat.	Name	Scale	D-Sub SMT, 25 poles Male, Straight with screw locks and ground pads		
			Detail.	25-Oct-11	Johnson.S				
			Insp.	17-Nov-11	Steven.W				
			Stand.	17-Nov-11	Steven.W				
EC04070	17-Nov-11	Johnson.S	Zhuhai HARTING Limited				TB 09 55 329 x82x		Page 2/2
Mod.	Dat.	Name					Sub.		