











THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN1570053	2015/06/01	Ruru	Change Logo



- Note:
- * Waterproof Rate: IP68
 - * Screw Nut: Nylon, Black
 - * Clamp Ring: Nylon, Black
 - * Sealing Nut: Nylon, Black
 - * Gasket: EPDM, Black
 - * Seals: EPDM, Black
 - * Panel Thickness: 6.2mm max
 - * Cable Range: $\varnothing 18\text{mm} \sim \varnothing 13\text{mm}$
 - * Spanner Size:
 - ① Screw Nut: 33mm
 - ③ Body: 32.5mm
 - ⑤ Sealing Nut: 34mm

UNIT: mm		TITLE		M25 Straight with SR		ITEM NO		DRAWN BY		DATE	
TOLERANCE		SCALE		SIZE		DWG NO		CHECKED BY		DATE	
.X ± 0.25		3:5		A4		CSG-25M005		Ruru		2015-06-01	
.XX ± 0.1		REV.		WC-REV.		CSG-25M005		Rita		2015-06-01	
.XXX ± 0.05		B		A.1		CUSTOMER		APPROVED BY		DATE	
ANGLES $\pm 1^\circ$						ALTW		Lion		2015-06-01	

Amphenol LTW
安費諾亮泰企業股份有限公司

QC: Inspection item