

Coaxial Cable Connector 16_N-50-7-53/133_N

Description

Right angle cable plug

Interface standards

IEC 61169-16_MIL-STD-348A/304_CECC 22210

Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 11 GHz

Mechanical Data

Centre contact soldered
Outer contact crimped
Weight 0.039347 kg

Environmental Data

Operating temperature -65 °C to 165 °C
2011/65/EU, RoHS compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Brass	SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00174541
Assembly instruction DOC-0000356242

Ordering Information

Bulk 100 pcs package 16_N-50-7-53/133_NH
Single package 16_N-50-7-53/133_NE

Additional Information

Suitable cables SPUMA_400-FR, SPUMA_400-UF