

This document is the property of Amphenol Corporation and is delivered on the understanding that it is for the sole use of the recipient for the manufacture or sale by anyone other than Amphenol Corporation. It is not to be distributed, copied, or used for any other purpose or for any other information in this document.



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A		07/11/07	

D-SUB TECHNICAL DATA

SHELL : Steel, 2.5um (100u") min tin over 1.25um (50u") min nickel
 BODY : Glass filled thermoplastic.
 Flame retardant to UL94 V-0
 CONTACTS : brass.
 0.76um(30u") min gold over 0.65um(25u") min nickel
 ELECTRICAL : Voltage rating :1000 V RMS at 50 Hz
 Current rating 5A.
 Insulation resistance >1000 M Ohms
 Contact resistance 20 mOhms max.
 CLIMATIC : Temperature range -55 °C up to 125°C
 MARKING : Amphenol...(Series No.)
 Commercial reference
 Manufacturing date

PRODUCT CODE

L 717 SD D 50 P C309



UNLESS OTHERWISE SPECIFIED		APPROVAL		DATE	
U.S.	METRIC	DRAWN	Iss. by	7/7/07	7/7/07
Tolerance	0.50	CHECKED	146.4000	7/7/07	7/7/07
FRACTIONS	0.30				
ANGLES	0.20				
FOR MATERIALS AND FINISHES SEE NOTES REMOVE SHARP EDGES					
DRAFTING FILE :					
ANGLE OF PROJECTION					
TITLE					
Stamped and Formed connector, SD series					
Amphenol					

DIMENSIONS		SCALE		SHEET	
U.S.	METRIC	SCALE	SCALE	SHEET	OF
MM	MM	A4	NONE	1	1

