

This document is the property of Amphenol Corporation and is delivered on the understanding that it is for the sole use of the recipient for the manufacture or sale by anyone other than Amphenol Corporation. No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or by any information storage or retrieval system, without the prior written permission of Amphenol Corporation. Amphenol Corporation reserves the right to change the specifications and dimensions of this product without notice. Amphenol Corporation is not responsible for any errors or omissions in this document or for any consequences arising from the use of the information contained herein.



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A		07/11/07	

D-SUB TECHNICAL DATA

SHELL : Steel, 2.5um (100u") min tin over 1.25um (50u") min nickel
 BODY : Glass filled thermoplastic.
 Flame retardant to UL94 V-0
 CONTACTS : brass.
 0.76um(30u") min gold over 0.05um(2u") min nickel
 ELECTRICAL : Voltage rating :1000 V RMS at 50 Hz
 Current rating 5A.
 Insulation resistance >1000 M Ohms
 Contact resistance 20 mOhms max.
 CLIMATIC : Temperature range -55 °C up to 125°C
 MARKING : Amphenol...(Series No.)
 Commercial reference
 Manufacturing date

PRODUCT CODE

L 717 SD D 50 P C309



UNLESS OTHERWISE SPECIFIED		APPROVAL		DATE	
U.S.	METRIC	DRAWN	Iss. by	7/7/07	7/7/07
T: ±0.50	0.50	CHECKED	146.4000	7/7/07	7/7/07
FRACTIONS ±0.20	0.20				
ANGLES ±0.2°	0.2°				

FOR MATERIALS AND FINISHES		DRAWING FILE :		TITLE	
U.S.	METRIC	U.S.	METRIC	Amphenol	
REMOVE SHARP EDGES				Stamped and Formed connector, SD series	
DIMENSIONS		ANGLE OF PROJECTION		SIZE DRAWING NO. C L717SDD50PC309	
U.S. DIMENSIONS				SCALE NONE SHEET 1 OF 1	
MM				REV. A	

