

This document is the property of Amphenol Corporation and is delivered on the understanding that it is not to be reproduced, stored in a retrieval system or used in any way for manufacturing or sales by anyone other than Amphenol Corporation. Amphenol Corporation reserves the right to make changes or to use any information in this document.



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A		07/11/07	

**D-SUB TECHNICAL DATA**

SHELL : Steel, 2.5um (100u") min tin over 1.25um (50u") min nickel  
 BODY : Glass filled thermoplastic.  
 Flame retardant to UL94 V-0  
 CONTACTS : brass.  
 0.76um(30u") min gold over 0.05um(20u") min nickel  
 ELECTRICAL : Voltage rating :1000 V RMS at 50 Hz  
 Current rating 5A.  
 Insulation resistance >1000 M Ohms  
 Contact resistance 20 mOhms max.  
 CLIMATIC : Temperature range -55 °C up to 125°C  
 MARKING : Amphenol...(Series No.)  
 Commercial reference  
 Manufacturing date

**PRODUCT CODE**

**L 717 SD D 50 P C309**



UNLESS OTHERWISE SPECIFIED		APPROVAL		DATE	
TOLERANCES		DRAWN	DATE	7/7/07	7/7/07
U.S.	METRIC	CHECKED	DATE	7/7/07	7/7/07
X	0.50				
XX	0.30				
XXX	0.20				
FRACTIONS					
ANGLES	2°				
FOR MATERIALS AND FINISHES SEE NOTES REMOVE SHARP EDGES					
DIMENSIONS					
U.S.	DIMENSIONS		ANGLE OF PROJECTION		
MM	MM		NONE		
TITLE					
Stamped and Formed connector, SD series					
SIZE		DRAWING NO.		REV.	
A4		C L717SDD50PC309		A	
SCALE		NONE		SHEET 1 OF 1	

