







DRAWN	K.WINCZURA	DATE 21/05/2013	 3RD ANGLE PROJECTION NOT TO SCALE	 POLAMCO LTD www.polamco.com	WESTON LOCK LOWER BRISTOL ROAD BATH BA2 1EP	THIS DRAWING IS COPYRIGHT AND THE PROPERTY OF POLAMCO LTD IT MUST NOT BE COPIED, USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT OF THE COMPANY.	
SALES APPR		21/05/2013					
DESIGN APPR	K.SHEPPARD	08/08/2013	UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN MILLIMETRES GENERAL TOL LINEAR +/-0.25MM ANGULAR +/- 1°	ASSY USED ON: MIL-DTL-38999 SERIES I & II			
PROD APPR				TITLE: THREAD ADAPTOR (DIRECT COUPLING)			
QUAL APPR							
ISSUE 1	DCR ---		MATERIAL SEE PART NUMBER BREAKDOWN FINISH SEE PART NUMBER BREAKDOWN	PART NUMBER: TM-D, TU-D, PG-D, NP-D SERIES	DRAWING NO: P25959	SHT 1	
NCAGE CODE U5792		WEIGHT ---					

TABLE 1

ORDER NUMBER	SHELL SIZE SERIES I	SHELL SIZE SERIES II	A THREAD	ØB MAX	ØT MIN
08	09	08	7/16-28UNEF	18,3	6,6
10	11	10	9/16-24UNEF	21,5	10,0
12	13	12	11/16-24UNEF	24,5	12,9
14	15	14	13/16-20UNEF	27,8	16,1
16	17	16	15/16-20UNEF	30,8	19,3
18	19	18	1 1/16-18UNEF	34,1	21,7
20	21	20	1 3/16-18UNEF	37,3	24,8
22	23	22	1 5/16-18UNEF	40,5	28,2
24	25	24	1 7/16-18UNEF	43,7	31,3

TABLE 2: METRIC THREAD (TM)

DASH NUMBER	R THREAD	ØG
16	M16x1.5	11,85
20	M20x1.5	15,85
22	M22x1.5	17,85
25	M25x1.5	20,85
32	M32x1.5	27,85
40	M40x1.5	35,85

TABLE 3: UNIFIED THREAD (TU)

DASH NUMBER	H THREAD	ØG MIN
04	7/16-28UNEF	6,35
05	1/2-20UNF	7,92
06	9/16-24UNEF	9,52
07	5/8-24UNEF	11,12
08	11/16-24UNEF	12,70
09	3/4-20UNEF	14,27
10	13/16-20UNEF	15,88
11	7/8-20UNEF	17,46
12	15/16-20UNEF	19,05
13	1-20UNEF	20,64
14	1 1/16-18UNEF	22,23
15	1 1/8-18UNEF	23,81
16	1 3/16-18UNEF	25,40
17	1 1/4-18UNEF	26,99
18	1 5/16-18UNEF	28,58
19	1 3/8-18UNEF	30,16
21	1 1/2-18UNEF	33,34
23	1 5/8-18UNEF	36,51

TABLE 4: PG THREAD (PG)

DASH NUMBER	C THREAD	ØG
7	PG7	8,0
9	PG9	10,6
11	PG11	14,0
13.5	PG13.5	15,8
16	PG16	17,9
21	PG21	23,5
29	PG29	32,1

TABLE 5: NPT THREAD (NP)

DASH NUMBER	Q THREAD DESIGNATION	ØG	L(M) MIN	L(F) MIN
0250	1/4 NPT	7,60	25,00	25,00
0375	3/8 NPT	11,00	26,00	26,00
0500	1/2 NPT	14,70	30,00	30,00
0750	3/4 NPT	20,00	30,00	30,00
1000	1 NPT	26,20	35,00	35,00
1250	1 1/4 NPT	35,00	36,00	36,00
1500	1 1/2 NPT	41,00	36,00	36,00
2000	2 NPT	53,00	37,00	37,00
2500	2 1/2 NPT	64,50	50,00	50,00

TABLE 6

CODE	MATERIAL / PLATING
1-C	ALUMINIUM / ELECTROLESS NICKEL
1-B	ALUMINIUM / CADMIUM OLIVE DRAB OVER ELECTROLESS NICKEL
1-ZB	ALUMINIUM / ZINC COBALT OLIVE DRAB OVER ELECTROLESS NICKEL
1-ZN	ALUMINIUM / ZINC NICKEL BLACK PASSIVATE OVER ELECTROLESS NICKEL
4-J	STAINLESS STEEL / PASSIVATE
2-Z	NICKEL ALUMINIUM BRONZE / SHOT BLAST

LIST NOT EXHAUSTIVE, SEE PLATING TABLE FOR OTHER OPTIONS

TMMF1-D16-20-1-C-L30

SERIES _____
 TM - METRIC THREAD
 TU - UNIFIED THREAD
 PG - PG THREAD
 NP - NPT THREAD
 ORIENTATION _____
 M - MALE
 F - FEMALE
 CONNECTOR INTERFACE _____
 ANGLE _____
 DIRECT COUPLING _____
 ORDER NUMBER (TABLE 1) _____
 DASH NUMBER _____
 DEPENDS ON THREAD - TABLE 2, 3, 4 & 5
 MATERIAL (TABLE 6) _____
 FINISH (TABLE 6) _____
 LENGTH CODE IN MM _____
 5MM INCREMENTS, MIN LENGTH 25,00MM,
 EXCEPT FOR NPT THREAD - SEE TABLE 5

DRAWN	K.WINCZURA	DATE 21/05/2013	 3RD ANGLE PROJECTION NOT TO SCALE	 POLAMCO LTD www.polamco.com	WESTON LOCK LOWER BRISTOL ROAD BATH BA2 1EP	THIS DRAWING IS COPYRIGHT AND THE PROPERTY OF POLAMCO LTD IT MUST NOT BE COPIED, USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT OF THE COMPANY	
SALES APPR		21/05/2013					
DESIGN APPR	K.SHEPPARD	08/08/2013					
PROD APPR							
QUAL APPR							
ISSUE 1	DCR ---		UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN MILLIMETRES GENERAL TOL LINEAR +/-0.25MM ANGULAR +/- 1°	ASSY USED ON: MIL-DTL-38999 SERIES I & II	TITLE: THREAD ADAPTOR (DIRECT COUPLING)		
		MATERIAL SEE PART NUMBER BREAKDOWN					
		FINISH SEE PART NUMBER BREAKDOWN					
NCAGE CODE U5792		WEIGHT ---				DRAWING NO: P25959	SHT 2