


**ALL NEW  
PRODUCTS!**

## Heyco® Nytye® Heavy Duty and Extra Heavy Duty/HVAC Nylon Cable Ties

| PART SPECIFICATIONS          |     |                      |       | PART NO.     |               | DESCRIPTION | PART DIMENSIONS |      |         |     |
|------------------------------|-----|----------------------|-------|--------------|---------------|-------------|-----------------|------|---------|-----|
| Max. Tensile Strength        |     | Max. Bundle Diameter |       | Natural      | UV Black      |             | A Length        |      | B Width |     |
| Lbs.                         | N   | in.                  | mm.   |              |               |             | in.             | mm.  | in.     | mm. |
| <b>Heavy Duty</b>            |     |                      |       |              |               |             |                 |      |         |     |
| 120                          | 534 | 1.30                 | 33,0  | <b>13172</b> | <b>13172B</b> | NT-120-059  | 5.91            | 150  | .30     | 7,6 |
|                              |     | 1.97                 | 50,0  | <b>13175</b> | <b>13175B</b> | NT-120-078  | 7.87            | 200  |         |     |
|                              |     | 2.48                 | 63,0  | <b>13178</b> | <b>13178B</b> | NT-120-098  | 9.84            | 250  |         |     |
|                              |     | 3.23                 | 82,0  | <b>13181</b> | <b>13181B</b> | NT-120-118  | 11.81           | 300  |         |     |
|                              |     | 3.54                 | 90,0  | <b>13183</b> | <b>13183B</b> | NT-120-137  | 13.78           | 350  |         |     |
|                              |     | 3.98                 | 101,0 | <b>13185</b> | <b>13185B</b> | NT-120-149  | 14.96           | 380  |         |     |
|                              |     | 4.13                 | 105,0 | <b>13186</b> | <b>13186B</b> | NT-120-157  | 15.75           | 400  |         |     |
| <b>Extra Heavy Duty/HVAC</b> |     |                      |       |              |               |             |                 |      |         |     |
| 175                          | 778 | .39                  | 10,0  | <b>13208</b> | <b>13208B</b> | NT-175-255  | 25.59           | 650  | .35     | 9,0 |
|                              |     |                      |       | <b>13215</b> | <b>13215B</b> | NT-175-315  | 31.50           | 800  |         |     |
|                              |     |                      |       | <b>13217</b> | <b>13217B</b> | NT-175-354  | 35.43           | 900  |         |     |
|                              |     |                      |       | <b>13218</b> | <b>13218B</b> | NT-175-393  | 39.37           | 1000 |         |     |
|                              |     |                      |       | <b>13220</b> | <b>13220B</b> | NT-175-477  | 47.76           | 1213 |         |     |

Standard colors natural and UV Black. Consult Heyco for heat-stabilized material and colors.

- Smooth, radiused edges ensure that Nytyes won't cut into the cable's insulation—or the installer's hand.
- One-piece design reduces cost and installation time.
- Nytyes feature a bent tip for ease of pickup and insertion around small bundles. V-shaped raised ridges on the tip provide a sure grip.
- Close, evenly spaced teeth permit fine adjustment—from .025" (0,6 mm) on the smallest Nytyes to .063" (1,6 mm) on the largest.
- Compliant with MS3367 and MIL-S-23190E



Material  
Certifications



Nylon 6/6  
Certified by UL for Compliance with both Canadian and U.S. requirements under File E54523

Flammability Rating  
Temperature Range

94V-2  
-40°F (-40°C) to 185°F (85°C)

*Quick  
Specs*