# XUDA1NSMM8



Main	
Range of product	OsiSense XU
Series name	Application assembly
Specific application of photoelectric detector	Object
Sensor name	XUD

### Complementary

oompiciliciliaiy		
Electronic sensor type	Photo-electric sensor	
Sensor design	Fiber design	
Enclosure material	PBT	
Wiring technique	3-wire	
Supply circuit type	DC	
Type of output signal	Discrete	
Output type	Solid state	
Discrete output function	1 NO or 1 NC programmable	
Discrete output type	NPN	
Electrical connection	1 male connector M8, 4 pins	
Cable material	PVC	
Status LED	1 LED red instability 1 LED yellow output state	
[Us] rated supply voltage	1224 V DC reverse polarity protection	
Supply voltage limits	10.826.4 V DC	
Current consumption	<= 50 mA (no-load)	
Switching capacity in mA	<= 100 mA overload protection <= 100 mA short-circuit protection	
Voltage drop	<= 1 V closed	
Switching frequency	<= 1 kHz	
Add on output	Without	
Delay first up	< 120 ms	
Delay response	< 0.5 ms	
Delay recovery	< 0.5 ms	
Product compatibility	Glass or plastic fibre optics 1 mm or 2.2 mm	
Setting-up	Sensitivity adjustment with teach mode	
Lens material	РММА	
Depth	0.39 in (10 mm)	
Height	2.56 in (65 mm)	
Width	1.57 in (40 mm)	
Product weight	0.09 lb(US) (0.04 kg)	

#### Environment

emission	Red	
interference protection	Without	
product certifications	CE CULus	
IP degree of protection	IP64 IEC 529 optic fiber Ø 1 mm	



	IP65 IEC 529 optic fiber Ø 2 mm
ambient air temperature for operation	14131 °F (-1055 °C)
ambient air temperature for storage	-22158 °F (-3070 °C)
vibration resistance	7 gn 1055 Hz) IEC 60068-2-6 +/-0.5 mm 1055 Hz) IEC 60068-2-6
shock resistance	30 gn (duration = 11 ms) conforming to IEC 60068-2-27

## **Offer Sustainability**

Not Green Premium product	Not Green Premium product	
Compliant - since 0623 - Schneider Electric declaration of conformity	Compliant - since 0623 - Schneider Electric declaration of conformity	
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:	
Diisononyl phthalate (DINP), which is known to the Stat of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	
Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm. harm.		
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov	

#### Contractual warranty

Warranty period

18 months

