

Applications

- Wireless Infrastructure
- AMPS, CDMA and TDMA
- General Purpose RF Filter
- 4G, Multi-Standard
- Band 1 Uplink
- Repeaters

Product Features

- 60 MHz Bandwidth
- High Attenuation
- Single-ended Operation
- 50 Ohm Impedance
- Small Size: 3.00 x 3.00 x 1.22 mm
- Ceramic Surface Mount Package (SMP)
- · Hermetically Sealed
- RoHS Compliant, Pb-Free (Pk

General Description

The 856678 is a Surface Acoustic Wave (SAW) based filter suitable for LTE Band 1 Uplink.

856678 is specifically designed to meet the high performance expectations of insertion loss and rejection for LTE downlink systems under all operating conditions.

This filter is housed in a compact, industry standard 3x3 mm footprint.

Low insertion loss, coupled with high attenuation makes this filter an ideal choice for Base Station Applications.

This filter is part of TriQuint's wide portfolio of RF filters.



856678

1950 MHz SAW Filter

SMP-12, 3.00 x 3.00 x 1.22 mm

Functional Block Diagram

Input

Gnd





Pin Configuration - Single Ended

Pin No.	Label
2	Input
5	Output
1.3,4,6	Ground

	Ordering	Information
--	----------	-------------

Part No.	Description			
856678	1950 MHz SAW Filter			
856678-EVB	Evaluation board			

Standard T/R size = 5000 units/reel



Absolute Maximum Ratings

Parameter	Rating
Storage Temperature ⁽¹⁾	−40 to +85 °C
Operable Temperature ⁽²⁾	−30 to +85 °C
DC Voltage (instantaneous only on any port)	+5 V

Notes:

1. Operation of this device outside the parameter ranges given may cause permanent damage.

2. Specifications are not guaranteed over all operable conditions.

Electrical Specifications (1,2,3)

Test conditions unless otherwise noted: ⁽²⁾ Temp= -30 °C to +85 °C

Parameter ⁽³⁾	Conditions	Min	Тур ⁽⁴⁾	Max	Units
Center Frequency		-	1950	-	MHz
Insertion Loss	1920 – 1980 MHz	-	1.8	3.0	dB
	1920 – 1980 MHz		0.45	1.6	
Amplitude Variation	1920 – 1980 MHz (over any 5 MHz band)		0.25	0.8	dB p-p
Phase Ripple	1920 – 1980 MHz		16	30	Deg.
Absolute Delay	1920 – 1980 MHz		11	50	ns
Group Delay Variation	1920 – 1980 MHz		6	30	ns p-p
Stopband Attenuation (relative to zero dB)	180 – 220 MHz 1470 – 1500 MHz 1500 – 1540 MHz 1540 – 1570 MHz 1570 – 1601 MHz 1601 – 1670 MHz 1814 – 1840 MHz 1840 – 1878 MHz 2025 – 2050 MHz	20 35 35 35 17 20 15 3	49 44.5 40.5 42 45.5 42 33 35.5 11.5 28		dB
	2100 – 2170 MHz 2490 – 3000 MHz 3213 – 3755 MHz 4925 – 5527 MHz	20 25 25 25	28 44 51.5 41.5	-	
Input/Output VSWR	1920 – 1980 MHz	1.5:1	2.2:1		-
Source Impedance ⁽⁵⁾	single-ended	-	50	-	Ohms
Load Impedance ⁽⁵⁾	single-ended	-	50	-	Ohms

Notes:

1. All specifications are based on the test circuit shown below.

2. Production test is performed at room temp. to a guard-banded specification to ensure electrical compliance over temperature.

3. Electrical margin has been built into the design to account for variation due to temperature drift and manufacturing tolerances.

4. Typical values are based on average measurements at room temperature

5. This is the optimum impedance in order to achieve the performance shown.



Evaluation Board

Matching Schematics



Notes:

- 1. No impedance matching required.
- 2. PCB: Top, middle & bottom layers: 1 oz copper, Substrates:FR4 dielectric, 031" thick Finish plating: Nickel: 3-8µm thick, Gold: .03-.2µm thick Hole plating: Copper min .0008µm thick

Bill of Material – 856678-EVB

Reference Des.	Value	Description	Manuf.	Part Number
DUT	-	1950 MHz SAW filter	TriQuint	856678
SMA	-	SMA connector	Radiall USA Inc.	9602-1111-018
PCB	-	3-Layer	Multiple	960700

PCB Mounting Pattern



Notes:

1. All dimensions are in millimeters. Angles are in degrees.

2. This drawing specifies the mounting pattern used on the TriQuint evaluation board for this product. Some modification may be necessary to suit end user assembly materials and processes.



856678 1950 MHz SAW Filter

Performance Plots

Test conditions unless otherwise noted: Temp= +25°C





Package Information, Marking and Dimensions



Package Style: SMP-12A

Body: AI_2O_3 ceramic Lid: *Kovar*, *Ni* plated Terminations: *Au* plating 0.5 - 1.0µm, over a 2-6µm *Ni* plating

The date code consists of JJJ =Julian day, Y = last digit of the year, and M = manufacturing site code

Notes:

- 1. All dimensions shown are typical in millimeters
- 2. All tolerances are ± 0.15 mm except overall length and width ± 0.10 mm
- 3. An asterisk (*) in front of the marking code indicates prototype.

Tape and Reel information

Standard T/R size = 5000 units/reel. All dimensions are in millimeters





Product Compliance Information

ESD Sensitivity Ratings



Caution! ESD-Sensitive Device

ESD Rating:	Class 0A
Value:	Passes ≤ 100 V
Test:	Electrostatic Discharge Sensitivity Testing,
	Human Body Model (HBM) - component level
Standard:	ESDA/JEDEC JS-001-2012

ESD Rating:	Class A
Value:	Passes ≤ 50 V
Test:	Machine Model (MM)
Standard:	JEDEC Standard JESD22-A115

MSL Rating

Not applicable. Hermetic package.

Solderability

Compatible with both lead-free (260°C maximum reflow temperature) and tin/lead (245°C maximum reflow temperature) soldering processes.

Refer to <u>Soldering Profile</u> for recommended guidelines.

RoHs Compliance

This part is compliant with EU 2002/95/EC RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment).

This product also has the following attributes:

- Lead Free
- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A (C₁₅H₁₂Br₄0₂) Free
- PFOS Free
- SVHC Free

Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations, and information about TriQuint:

Web:	www.triguint.com	Tel:
Email:	info-sales@tqs.com	Fax:

Tel: +1.407.886.8860 Fax: +1.407.886.7061

For technical questions and application information:

Email: <u>flapplication.engineering@tqs.com</u>

Important Notice

The information contained herein is believed to be reliable. TriQuint makes no warranties regarding the information contained herein. TriQuint assumes no responsibility or liability whatsoever for any of the information contained herein. TriQuint assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for TriQuint products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

TriQuint products are not warranted or authorized for use as critical components in medical, life-saving, or lifesustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.