FO-55111-A

REV	DOCUMENT	CHANGED BY	CHECK
7	0038225	PRS 09APR08	BLR

HONEYWELL PART NUMBER
111SM244
PRODUCT CODE TYJ6000



NOTE –

1 – MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .087 MAX DIA ON .375±.002 CENTERS

2 – TERMINALS ARE PLATED FOR SOLDERING

3 – SWITCH WILL WITHSTAND TEMPERATURE OF 400° F

RELEASE NO.
SR - 12442
REPLACES -

CHARACTERISTICS
OPERATING FORCE – – – – 7 OZ MAX
RELEASE FORCE – – – – – 2 OZ MIN
DIFFERENTIAL TRAVEL – – – .030 MAX
OVERTRAVEL – – – – – – .030 MIN

ELECTRICAL DATA			
CONTACT ARRANGEMENT SPDT			
30 VOLTS DC RATING			
		SEA LEVEL	50,000 FT
	INDUCTIVE	3 AMP	2.5 AMP
	RESISTIVE	5 AMP	5 AMP
MAXIMUM INRUSH 24 AMP			
APPROVALS	KEMA, CE	5A, 250V ~ T85 1E4	
	UL, CSA	5A, 250 VAC	BRAND L4

DESIGN UNITS: INCH

TOLERANCES UNLESS NOTED:

NO PLACE	X	±	-
ONE PLACE	.X	±	0.030
TWO PLACE	.XX	±	0.015
THREE PLACE	.XXX	±	0.005
FOUR PLACE	.XXXX	±	-
ANGLES		±	-

THIRD ANGLE PROJECTION

DRAWN	VK	29 OCT 07
CHECK	RJ	29 OCT 07

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.

INTERPRET PER ANSI Y14.5M-1982 OTHER HONEYWELL ENGINEERING STANDARDS MAY APPLY

RASTER

Honeywell

TITLE

SWITCH - BASIC

SIZE	TYPE	DRAWING NAME	REV
B	I	111SM244	7
SCALE -		WEIGHT .006 LB MAX	SHEET 1 OF 1