








THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	C190347	2019/03/06	Vicky	Change Note



- Note:**
- * **QC** Important Dimension To Check.
 - * Waterproof Rate: IP67, Unmated.
 - * Housing: Thermoplastic, Black.
 - * Pin: Copper Alloy, Gold Plated.
 - * Gasket: Rubber, Gray.
 - * Nut: Thermoplastic, Black.
 - * Use with waterproof cap or dust cap
Maximum Panel Thickness: 1.8mm
 - * Use without waterproof cap or dust cap
Maximum Panel Thickness: 3.0mm
 - * Gasket and Nut are packed separately in PE bags. (Gasket/Nut不組裝，散裝出貨)

UNIT: mm		TOLERANCE		TITLE		ITEM NO.		DRAWN BY		DATE	
.X ±0.25		.XX ±0.1		LARGE		ADD-18PMMS-LS7001		Vicky		2019-03-06	
.XXX ±0.05		ANGLES ±1°		PANEL LOCK 18P M CONN M PIN		DWG NO		CHECKED BY		DATE	
				SCALE 1:1		ADD-18PMMS-LS7001		Rita		2019-03-06	
				REV. B		CUSTOMER		APPROVED BY		DATE	
				WC-REV. A.1		ALTW		Max		2019-03-06	
				QC: Inspection item							

Amphenol LTW
安費諾亮泰企業股份有限公司