

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	22JUN2017	DW	CW

WIRE RANGE

M25X 1.5

(26)

7

28

Ø 31

NOTES / 注解:

1. TECHNICAL CHARACTERISTICS / 技术参数:

SHELL MATERIAL / 主体材料: NICKEL PLATED BRASS / 铜镀镍

SEAL MATERIAL / 密封材料: RUBBER, BLACK

PINCH RING MATERIAL / 夹紧件材料: NYLON, GREY

OPERATION TEMPERATURE / 工作温度: -40°C - +100°C

PROTECTION DEGREE / 防护等级: IP68

WIRE RANGE / 夹线范围: 11-16 mm

T3707250113-000

DLX-25-MTC (11-16)
电磁屏蔽金属接头 M25 (11-16)PART NUMBER
料号PART DESCRIPTION
描述

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 22JUN2017

DAVID WANG

CHK 22JUN2017

GINO YAO

APVD 22JUN2017

CHRIS WANG

PRODUCT SPEC

-

APPLICATION SPEC

-

WEIGHT

-

CUSTOMER DRAWING

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±-
2 PLC	±-
3 PLC	±-
4 PLC	±-
ANGLES	±-

MATERIAL

-

FINISH

-

TE Connectivity

NAME
DLX-25-MTC (11~16)

SIZE

A3

CAGE CODE

-

DRAWING NO

T3707250113000

RESTRICTED TO

-

SCALE

3:2

SHEET

1 OF 1

REV

A

1470-19 (3/13)