

Housing - HC-EVO-D15-HHFS-PL-BK - 1411340

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



HEAVYCON EVO sleeve housing, plastic, with bayonet flange for EVO screw connection, D15 series, for single locking latch, height: 65.5 mm, without EVO screw connection

Product Features

- Flexible cable outlet direction, lateral or straight

- Both contact insert PE sheets are connected by means of a metal frame integrated in the sleeve housing
- Metal inlays ensure leading PE contact with angled plugs
- Completely corrosion-resistant

- $\overline{\mathbf{M}}$



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	60.0 GRM
Custom tariff number	85389099
Country of origin	Poland

Technical data

Dimensions

Height	65.5 mm
Width	30 mm
Length	63.5 mm

Ambient conditions



Housing - HC-EVO-D15-HHFS-PL-BK - 1411340

Technical data

Ambient conditions

Degree of protection of housing (IP)	IP66	
Degree of protection of housing (NEMA)	4 (UL50e / NEMA 250)	
	4X (UL50e / NEMA 250)	
	12 (UL50e / NEMA 250)	
Ambient temperature (operation)	-40 °C 125 °C	

General

Note	For contact inserts HC-D15, A10		
Туре	D15		
Housing type	Sleeve housing		
Color	black		
Locking type	for single locking latch		
No. of cable outlets	1		
Cable exit	straight		
	Lateral		
Screw connection	none		
Housing material	Polyamide		
Inflammability class according to UL 94	V0		
Connection	The sleeve base housing must be supplemented with the EVO screw connection. The EVO screw connection is available in 4 sizes. It enables the creation of a straight or lateral cable outlet. The EVO screw connection is mounted by hand or with the aid of a pipe wrench, for example.		

Classifications

eCl@ss

eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 8.0	27440202

ETIM

ETIM 4.0	EC000437
ETIM 5.0	EC000437

Approvals


Approvals



Housing - HC-EVO-D15-HHFS-PL-BK - 1411340

Approvals			
Approvals			
EAC / GL			
Ex Approvals			
Approvals submitted			
Approval details			
EAC			
GL			
Drawings			

Dimensional drawing



Dimensional drawing

Phoenix Contact 2015 © - all rights reserved http://www.phoenixcontact.com