



Main

Range of product	Harmony XK
Product or component type	Complete joystick controller
Device short name	XDP
Mounting diameter	48 mm
Bezel material	Plastic
Sale per indivisible quantity	1

Complementary

Operator position information	2 positions
Operator direction information	1 direction
Contacts type and composition	2 NO
Contacts usage	Standard
Mechanical durability	1000000 cycles
Return	Spring return
Height	158.6 mm
Width	2.56 in (65 mm)
Depth	1.73 in (44 mm)
Product weight	1.1 lb(US) (0.5 kg)

Environment

standards	EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5 JIS C 4520 UL 508 CSA C22.2 No 14
ambient air temperature for operation	-40...140 °F (-40...60 °C)
IP degree of protection	IP65

Offer Sustainability

Not Green Premium product	Not Green Premium product
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.