



Main

Range of product	TeSys
Device short name	GS1AN
Product or component type	Auxiliary contact
Contact application	O and I position signalling
Contacts type and composition	1 NC + 1 NO
Contact operation	Instantaneous
[Ith] conventional free air thermal current	20 A at 104 °F (40 °C)
[Ie] rated operational current	1 A at 220 V DC-13 10 A at 230 V AC-15 12 A at 127 V AC-15 4 A at 48 V DC-13 6 A at 440 V AC-15 8 A at 400/415 V AC-15 1.2 A at 110 V DC-13

Complementary

Mechanical durability	30000 cycles
Electrical durability	30000 cycles on AC-15
Product compatibility	GS
Line Rated Current	1250 A 100 A 125 A 160 A 200 A 250 A 315 A 400 A 50 A 60 A 600 A 63 A 630 A 800 A
Fuse type	BS DIN NFC
Type of operating handle	Direct frontal Direct right side External frontal External right side
Product weight	0.29 lb(US) (0.132 kg)

Environment

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1650 - Schneider Electric declaration of conformity	Compliant - since 1650 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
WARNING: Cancer - www.P65Warnings.ca.gov	WARNING: Cancer - www.P65Warnings.ca.gov

Auxiliary Contacts - 1 N/C + 1 N/O

14 13
22 21