


Für Layerout - Maßstab 1:1



Layoutvorgabe (Ansicht PCB)

Lochspezifikation:

- o Bohrdurchmesser: $\phi 3,00^{+0,00}_{-0,03}$
 Enddurchmesser chem. Zinn: $\phi 2,875^{+0,05}_{-0,05}$
 (Cu: min. 30 μ m - max. 60 μ m)
- Enddurchmesser HAL bleifrei: $\phi 2,85^{+0,05}_{-0,05}$
 (Cu: min. 25 μ m, Sn: max. 15 μ m)
- x Bohrdurchmesser: $\phi 3,20^{+0,00}_{-0,03}$
 Enddurchmesser: $\phi 3,10^{+0,04}_{-0,06}$

Copyright by ERNI GmbH
 Proprietary notice pursuant to ISO 16016 to be observed.

Material / Surface		Tolerances		Scale	2:1	Original drawing		
		 All Dimensions in mm		Drawing Number				225416
		Drawn	15.03.12	M.Tolj	Designation			ERNI BCS Powerelement Buchse M8
		Checked	15.03.12	T.Engel	Customer Part Number			
		Approved						
A	Neuerstellung	15.03.12	M.Tolj	 Electronics GmbH BLUEcontact Solutions D-73099 ADELBERG		A4		
Index	Modification Nr.	Date	Name					

108020003

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ERNI Electronics:](#)

[225416](#)