

Coaxial Cable Connector

24_716-50-0-1/003_-

Description

Straight bulkhead cable feed through

Interface standards

IEC 61169-4_CECC 22190_DIN 47223_VG 95250



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	7.5 GHz

Mechanical Data

Centre contact	soldered
Weight	0.1257 kg

Environmental Data

Operating temperature	-50 °C to 160 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Bronze / Brass	Silver Plating
Outer contact	Brass	Silver Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	NR (Natural Rubber)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Brass	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00009866
Catalogue drawing	DCA-00009868
Mounting hole	DOU-00008772

Ordering Information

Tray package	24_716-50-0-1/003_-Y
--------------	----------------------

Additional Information

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[24_716-50-0-1/003_-Y](#)