



*Quality Products. Service Excellence.*

## Type 4X Stainless Steel Freestanding Enclosure 1418 N4 FS SS Series

Continuous Hinge Door with Clamps



### Application

- Designed to house electrical, electronic, hydraulic or pneumatic controls with provision for panel mounting or rack mounting of equipment.
- Provides protection where equipment may be hosed down or otherwise be very wet, or in specific applications where corrosion is a serious problem.
- A variety of inner panels, rack mounting rails and swing out frames are available to provide flexibility in mounting arrangements.

### Standards

- UL 508A Type 3R, 4, 4X and 12
- CSA Type 3R, 4, 4X and 12
- Complies with
  - NEMA Type 3R, 4, 4X, 12 and 13
  - IEC 60529, IP66

### Construction

- Formed 12 gauge 304 or 316 stainless steel.
- Smooth, continuously welded seams without knockouts, cutouts or holes.
- Heavy duty stainless steel lifting eyebolts are provided with reinforcing support angles.
- Doors are supported with heavy gauge continuous hinges.
- Doors are secured with heavy duty stainless steel clamps.
- Seamless poured-in place gasket.
- Mounting channels are welded on the inside of the enclosure for mounting of optional inner panels or rack equipment rails.
- A grounding stud is provided in the enclosure and a bonding stud is provided on the door.

### Finish

- Cover and enclosure are natural stainless steel with a smooth brushed finish.
- Optional inner panels are finished in white powder paint.

### Accessories

- Inner Panels
- Swing Out Frames
- Drip Shield Kit
- Climate Control
- Lighting
- Panel Rails
- Door Stop Kit
- Door Clamping Hardware
- Window Kits
- General Accessories

| 304 S.S.<br>Part No. | 316 S.S.<br>Part No. | Enclosure |       |       | Optional Full Size<br>Inner Panel |
|----------------------|----------------------|-----------|-------|-------|-----------------------------------|
|                      |                      | H         | W     | D     |                                   |
| 1418N4SSW18          | 1418N4S16W18         | 72.06     | 25.06 | 18.06 | 72WFW                             |
| 1418N4SSX24          | 1418N4S16X24         | 72.06     | 31.06 | 24.06 | 72XFW                             |
| 1418N4SSY24          | 1418N4S16Y24         | 72.06     | 37.06 | 24.06 | 72YFW                             |

Alternative inner panel options also available.

*Data subject to change without notice*

© 2020. Hammond Manufacturing Ltd. All rights reserved.