

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

15268-0305

Status:

Active

Overview:

Premo-Flex™ FFC and Etched Polyimide Jumpers

Description:

1.25mm Pitch Premo-Flex™ FFC Jumper, Same Side Contacts (Type A), 24 Circuits, 0.102m Cable Length, 0.27mm Cable Thickness, Tin (Sn) Plating

Documents:

Drawing (PDF)

Product Specification PS-15268-001 (PDF)

Packaging Specification PK-15268-001 (PDF)

RoHS Certificate of Compliance (PDF)

|                                    |                                              |
|------------------------------------|----------------------------------------------|
| <b>General</b>                     |                                              |
| Product Family                     | Cable                                        |
| Series                             | 15268                                        |
| Comments                           | Contacts on the same side, Type A            |
| Crimp Quality Equipment            | Yes                                          |
| Overview                           | Premo-Flex™ FFC and Etched Polyimide Jumpers |
| Product Name                       | Premo-Flex™ FFC Jumper                       |
| UPC                                | 884982426344                                 |
| <b>Physical</b>                    |                                              |
| Cable Length                       | 0.102m                                       |
| Circuits (Loaded)                  | 24                                           |
| Circuits (maximum)                 | 24                                           |
| Net Weight                         | 2.157/g                                      |
| Packaging Type                     | Bag                                          |
| Pitch - Termination Interface      | 1.25mm                                       |
| Temperature Range - Operating      | -40°C to +105°C                              |
| Wire Size AWG                      | N/A                                          |
| Wire/Cable Type                    | Flat Flex Cable                              |
| <b>Electrical</b>                  |                                              |
| Current - Maximum per Contact      | 1.4A                                         |
| Voltage - Maximum                  | 60V AC                                       |
| <b>Material Info</b>               |                                              |
| <b>Reference - Drawing Numbers</b> |                                              |
| Packaging Specification            | PK-15268-001                                 |
| Product Specification              | PS-15268-001                                 |
| Sales Drawing                      | SD-15268-001                                 |



image - Reference only

Series

**EU RoHS**

**ELV and RoHS**

**Compliant**

**REACH SVHC**

**Not Reviewed**

**Low-Halogen Status**

**Not Reviewed**

**China RoHS**



**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**

15268Series

**Use With**

<a href="www.molex.com/link/ffc-fpc.html">Molex FFC – FPC connector</a>.  
Be sure to match like plating

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION