

## 7852A Multi-Conductor - Enhanced Category 6 Bonded-Pair Cable



For more Information  
please call

1-800-Belden1

**General Description:**

CAT6+ (600MHz), 4-Bonded-Pairs, U/UTP-Unshielded, Plenum-CMP, Premise Horizontal Cable, 23 AWG Solid Bare Copper Conductors, FEP Insulation, Patented E-Spline, Ripcord, Flamarrest® Jacket

**Usage (Overall)****Suitable Applications:**

Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422, Noisy Environments

**Physical Characteristics (Overall)****Conductor****AWG:**

| # Pairs | AWG | Stranding | Conductor Material |
|---------|-----|-----------|--------------------|
| 4       | 23  | Solid     | BC - Bare Copper   |

**Total Number of Conductors:**

8

**Insulation****Insulation Material:**

| Insulation Material                  |
|--------------------------------------|
| FEP - Fluorinated Ethylene Propylene |

**Outer Shield****Outer Shield Material:**

| Outer Shield Material |
|-----------------------|
| Unshielded            |

**Outer Jacket****Outer Jacket Material:**

| Outer Jacket Trade Name | Outer Jacket Material                 |
|-------------------------|---------------------------------------|
| Flamarrest®             | LS PVC - Low Smoke Polyvinyl Chloride |

**Outer Jacket Diameter:**

| Nom. Dia. (mm) |
|----------------|
| 6.477          |

**Outer Jacket Ripcord:**

Yes

**Overall Cable****Overall Cabling Separator Material:**

Patented E-Spline Center Member

**Overall Nominal Diameter:**

5.537 x 7.366 mm

**Pair****Pair Color Code Chart:**

| Number | Color                        |
|--------|------------------------------|
| 1      | White/Blue Stripe & Blue     |
| 2      | White/Orange Stripe & Orange |
| 3      | White/Green Stripe & Green   |
| 4      | White/Brown Stripe & Brown   |

**Mechanical Characteristics (Overall)****Storage Temperature Range:**

-20°C To +75°C

**7852A Multi-Conductor - Enhanced Category 6 Bonded-Pair Cable**

|                                   |               |
|-----------------------------------|---------------|
| Installation Temperature Range:   | +5°C To +50°C |
| Operating Temperature Range:      | 0°C To +75°C  |
| Bulk Cable Weight:                | 55.063 Kg/Km  |
| Max. Recommended Pulling Tension: | 200.169 N     |
| Min. Bend Radius/Minor Axis:      | 12.700 mm     |
| Min. Bend/Installation:           | 57.150 mm     |

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

|                                       |                          |
|---------------------------------------|--------------------------|
| NEC/(UL) Specification:               | CMP                      |
| NEC Articles:                         | 800                      |
| CEC/C(UL) Specification:              | CMP                      |
| EU Directive 2011/65/EU (ROHS II):    | Yes                      |
| EU CE Mark:                           | Yes                      |
| EU Directive 2000/53/EC (ELV):        | Yes                      |
| EU Directive 2002/95/EC (RoHS):       | Yes                      |
| EU RoHS Compliance Date (mm/dd/yyyy): | 07/01/2006               |
| EU Directive 2002/96/EC (WEEE):       | Yes                      |
| EU Directive 2003/11/EC (BFR):        | Yes                      |
| CA Prop 65 (CJ for Wire & Cable):     | Yes                      |
| MII Order #39 (China RoHS):           | Yes                      |
| Telecommunications Standards:         | Category 6 - TIA 568.C.2 |

**Applicable Patents:**

| Country | Patent  |
|---------|---------|
| US      | 5606151 |
| US      | 6064503 |
| US      | 6885889 |
| US      | 7663061 |
| US      | 7838773 |
| US      | 7977575 |
| US      | 8536455 |

**Flame Test**

|                   |                                         |
|-------------------|-----------------------------------------|
| UL Flame Test:    | NFPA 262 Plenum Flame Test (UL910)(FT6) |
| C(UL) Flame Test: | FT6                                     |
| CSA Flame Test:   | FT6                                     |

**Plenum/Non-Plenum**

|                    |       |
|--------------------|-------|
| Plenum (Y/N):      | Yes   |
| Non-Plenum Number: | 7851A |

**Electrical Characteristics (Overall)****Nom. Mutual Capacitance:**

| Capacitance (pF/m) |
|--------------------|
| 50.8555            |

|                                           |    |
|-------------------------------------------|----|
| Maximum Capacitance Unbalance (pF/100 m): | 90 |
|-------------------------------------------|----|

**Nominal Velocity of Propagation:**

| VP (%) |
|--------|
| 67     |

## 7852A Multi-Conductor - Enhanced Category 6 Bonded-Pair Cable

### Maximum Delay:

| Delay (ns/100 m) |
|------------------|
| 538 @ 100MHz     |

### Max. Delay Skew:

| Delay Skew (ns/100 m) |
|-----------------------|
| 38                    |

### Maximum Conductor DC Resistance:

| DCR @ 20°C (Ohm/100 m) |
|------------------------|
| 8.2                    |

### Max. Operating Voltage - UL:

| Voltage   |
|-----------|
| 300 V RMS |

### Maximum DCR Unbalanced:

| DCR Unbalance @ 20°C (%) |
|--------------------------|
| 3                        |

## Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

| Freq. (MHz) | Max. Attenuation (dB/100 m) | Min. NEXT (dB) | Min. PSNEXT (dB) | Min. ACR (dB) | Min. PSACR (dB) | Min RL (dB) |
|-------------|-----------------------------|----------------|------------------|---------------|-----------------|-------------|
| 1           | 1.900                       | 82.3           | 80.3             | 80.5          | 78.5            | 20.000      |
| 4           | 3.600                       | 73.3           | 71.3             | 69.7          | 67.7            | 23.000      |
| 8           | 5.100                       | 68.8           | 66.8             | 63.7          | 61.7            | 24.500      |
| 10          | 5.700                       | 67.3           | 65.3             | 61.6          | 59.6            | 25.000      |
| 16          | 7.200                       | 64.3           | 62.3             | 57.0          | 55.0            | 25.000      |
| 20          | 8.100                       | 62.8           | 60.8             | 54.7          | 52.7            | 25.000      |
| 25          | 9.100                       | 61.3           | 59.3             | 52.3          | 50.3            | 25.000      |
| 31.25       | 10.200                      | 59.9           | 57.9             | 49.7          | 47.7            | 25.000      |
| 62.5        | 14.700                      | 55.4           | 53.4             | 40.7          | 38.7            | 25.000      |
| 100         | 18.900                      | 52.3           | 50.3             | 33.4          | 31.4            | 25.000      |
| 155         | 23.900                      | 49.5           | 47.5             | 25.5          | 23.5            | 22.800      |
| 200         | 27.500                      | 47.8           | 45.8             | 20.3          | 18.3            | 21.600      |
| 250         | 31.200                      | 46.3           | 44.3             | 15.2          | 13.2            | 20.500      |
| 300         | 34.500                      | 43.2           | 43.2             | 8.6           | 8.6             | 20.200      |
| 350         | 37.700                      | 42.1           | 42.1             | 4.4           | 4.4             | 19.800      |
| 400         | 40.600                      | 41.3           | 41.3             | 0.7           | 0.7             | 19.500      |
| 450         | 43.500                      | 40.5           | 40.5             | 0             | 0               | 18.900      |
| 460         | 44.000                      | 40.4           | 40.4             | 0             | 0               | 18.800      |
| 500         | 46.200                      | 39.8           | 39.8             |               |                 | 18.400      |
| 550         | 48.800                      | 39.2           | 39.2             |               |                 | 18.000      |
| 600         | 51.400                      | 38.6           | 38.6             |               |                 | 17.600      |

Premise Cable Electrical Table 2:

| Freq. (MHz) | Input (Unfitted) Imp. (Ohms) | Fitted Impedance | Min. ACRF (dB) | Min. PSACRF (dB) |
|-------------|------------------------------|------------------|----------------|------------------|
| 1           | 100 ± 12                     | 100 ± 15         | 74.8           | 72.8             |
| 4           | 100 ± 12                     | 100 ± 10.4       | 62.8           | 60.8             |
| 8           | 100 ± 12                     | 100 ± 8          | 56.7           | 54.7             |
| 10          | 100 ± 12                     | 100 ± 7.3        | 54.8           | 52.8             |
| 16          | 100 ± 12                     | 100 ± 5.7        | 50.7           | 48.7             |
| 20          | 100 ± 12                     | 100 ± 5          | 48.8           | 46.8             |
| 25          | 100 ± 15                     | 100 ± 5          | 46.8           | 44.8             |
| 31.25       | 100 ± 15                     | 100 ± 5          | 44.9           | 42.9             |
| 62.5        | 100 ± 15                     | 100 ± 5          | 38.9           | 36.9             |
| 100         | 100 ± 15                     | 100 ± 5          | 34.8           | 32.8             |
| 155         | 100 ± 15                     | 100 ± 5          | 31.0           | 29.0             |
| 200         | 100 ± 15                     | 100 ± 5          | 28.8           | 26.8             |
| 250         | 100 ± 20                     | 100 ± 5          | 26.8           | 24.8             |
| 300         | 100 ± 20                     | 100 ± 5          | 25.3           | 23.3             |
| 350         | 100 ± 22                     | 100 ± 5          | 23.9           | 21.9             |

## METRIC MEASUREMENT VERSION

## 7852A Multi-Conductor - Enhanced Category 6 Bonded-Pair Cable

|     |          |         |      |      |
|-----|----------|---------|------|------|
| 400 | 100 ± 22 | 100 ± 5 | 22.8 | 20.8 |
| 450 | 100 ± 22 | 100 ± 5 | 21.7 | 19.7 |
| 460 | 100 ± 22 | 100 ± 5 | 21.5 | 19.5 |
| 500 | 100 ± 22 | 100 ± 5 | 20.8 | 18.8 |
| 550 | 100 ± 22 | 100 ± 5 | 20.0 | 18.0 |
| 600 | 100 ± 22 | 100 ± 5 | 19.2 | 17.2 |

## Notes (Overall)

**Notes:** Belden IBDN. Jacket sequentially marked at 2 ft./1m intervals. Third party verified to ANSI/TIA-568-C.2, Category 6.

## Put Ups and Colors:

| Item #         | Putup  | Ship Weight | Color       | Notes | Item Desc                  |
|----------------|--------|-------------|-------------|-------|----------------------------|
| 7852A D15A1000 | 305 MT | 19.958 KG   | BLUE        |       | CAT6E+ 4PRB U/UTP CMP RIB  |
| 7852A D151000  | 305 MT | 18.597 KG   | BLUE        | C     | CAT6E+ 4PRB U/UTP CMP REEL |
| 7852A 0021000  | 305 MT | 18.597 KG   | RED         |       | CAT6E+ 4PRB U/UTP CMP REEL |
| 7852A 003A1000 | 305 MT | 19.958 KG   | ORANGE      | C     | CAT6E+ 4PRB U/UTP CMP RIB  |
| 7852A 0031000  | 305 MT | 18.597 KG   | ORANGE      | C     | CAT6E+ 4PRB U/UTP CMP REEL |
| 7852A 004A1000 | 305 MT | 19.958 KG   | YELLOW      |       | CAT6E+ 4PRB U/UTP CMP RIB  |
| 7852A 0041000  | 305 MT | 18.597 KG   | YELLOW      | C     | CAT6E+ 4PRB U/UTP CMP REEL |
| 7852A 005A1000 | 305 MT | 19.958 KG   | GREEN, DARK |       | CAT6E+ 4PRB U/UTP CMP RIB  |
| 7852A 0051000  | 305 MT | 18.597 KG   | GREEN, DARK | C     | CAT6E+ 4PRB U/UTP CMP REEL |
| 7852A 008A1000 | 305 MT | 19.958 KG   | GRAY        |       | CAT6E+ 4PRB U/UTP CMP RIB  |
| 7852A 0081000  | 305 MT | 18.597 KG   | GRAY        |       | CAT6E+ 4PRB U/UTP CMP REEL |
| 7852A 009A1000 | 305 MT | 19.958 KG   | WHITE       |       | CAT6E+ 4PRB U/UTP CMP RIB  |
| 7852A 0091000  | 305 MT | 18.597 KG   | WHITE       | C     | CAT6E+ 4PRB U/UTP CMP REEL |
| 7852A 0101000  | 305 MT | 18.597 KG   | BLACK       |       | CAT6E+ 4PRB U/UTP CMP REEL |

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 8    Revision Date: 01-06-2014

© 2014 Belden, Inc  
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.