

Product data sheet

Characteristics

8501KA112AV14

Alternating plug in relay, 11 pin, DPDT (NO),
24 VAC/DC coil



Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Product range	8501KA
Product type	Plug-in relay
Relay type	Alternating
Contact composition	NO - DPDT
[Uc] control circuit voltage	24 V AC/DC
Horsepower rating	0.33 Hp 120 V AC 0.5 hp 240 V AC
Breaking capacity	3 A 120 V AC inductive control circuit UL 508 1.5 A 240 V AC inductive control circuit UL 508 5 A 120 V AC resistive control circuit UL 508 12 A 30 V DC resistive control circuit UL 508
Mounting type	Socket
Pilot light	Green indicator relay energised LED
Control type	Toggle switch

Complementary

Maximum switching voltage	240 V AC
Number of pins	11
Shape of pins	Tubular
For use with	8501NR62 8501NR61

Environment

Product certifications	UL recognized UL listed CSA RoHS CE
Height	1.73 in (44 mm)
Width	1.42 in (36 mm)
Depth	3.29 in (83.5 mm)

Ordering and shipping details

Category	21145 - 8501 KF,KL
Discount Schedule	CP2
GTIN	00785901823742
Package weight(Lbs)	0.11 kg (0.25 lb(US))
Returnability	No
Country of origin	CN

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------