



TABLE A				
CABLE TYPE	DIMENSION A	DIMENSION B	DIMENSION C	SPACER REQUIRED
LMR-240	5.15 [.203]	7.70 [.303]	16.00 [.630]	YES
RG-8/X	4.00 [.157]	7.70 [.303]	16.00 [.630]	NO

10	FERRULE	BRASS	NICKEL	1
9	SPACER	PTFE	NATURAL	1
8	CONTACT PIN	BRASS	GOLD	1
7	WASHER	BRASS	NICKEL	1
6	RING	DELTRIN	NATURAL	1
5	RETAINER RING	BRASS	NICKEL	1
4	GASKET	RUBBER	RED	1
3	INSULATOR	DELTRIN	NATURAL	1
2	BODY	BRASS	NICKEL	1
1	SHELL	BRASS	NICKEL	1
	DESCRIPTION	MATERIAL	FINISH	QTY

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE
IN MILLIMETERS. DIMENSIONS IN [] ARE IN
INCHES AND FOR CUSTOMER REFERENCE ONLY.

UNLESS OTHERWISE SPECIFIED
TOLERANCES FOR MILLIMETERS ARE:

0.5	-	6mm	±	0.05mm
6	-	30mm	±	0.10mm
30	-	120mm	±	0.20mm
				± 0.30mm
ANGLES				± 1°

UNLESS OTHERWISE SPECIFIED
TOLERANCES FOR INCHES ARE:

<.020	± 0.002"
.020 - .236	± 0.004"
.236 - 1.180	± 0.007"
1.180 - 4.724	± 0.012"

ANGLES ± 1°

DO NOT SCALE DRAWING

	APPROVALS	DATE
DRAWN	M.ZHANG	12/02/13
CHECKED		
ISSUED		
SHEET	1 OF 1	
CAD FILE		
C:/CONNEX/122408.DWG		

Amphenol Connex

PART	DESCRIPTION	QTY	UNIT	PRICE	AMOUNT	TAX	TOTAL
1	PART DESCRIPTION						
2							
3							
4							
5							
6							
7							
8							
9							
10							
11							
12							
13							
14							
15							
16							
17							
18							
19							
20							

TNC CRIMP PLUG
(FOR RG-8/X, LMR-240 CABLE)

	PART NO.
--	----------

122408

DWG. NO. 122408.DWG

REV.	F
------	---

SIZE	A
------	---

SCALE	NA
-------	----