


## VERONICA-SQ-W

~50° wide beam

### TECHNICAL SPECIFICATIONS:


|                |   |
|----------------|---|
| Dimensions     | 22.5 mm   |
| Height         | 11.8 mm   |
| Fastening      | tape  |
| ROHS compliant | yes  |


### MATERIAL SPECIFICATIONS:

| Component     | Type        | Material | Colour | Finish |
|---------------|-------------|----------|--------|--------|
| VERONICA-SQ-W | Single lens | PMMA     | clear  |        |
| VERONICA-TAPE | Tape        | PU tape  | clear  |        |

### ORDERING INFORMATION:

| Component                      |             | Qty in box | MOQ | MPQ | Box weight (kg) |
|--------------------------------|-------------|------------|-----|-----|-----------------|
| CA14442_VERONICA-SQ-W          | Single lens | 1980       | 360 | 180 | 8.8             |
| » Box size: 476 x 273 x 197 mm |             |            |     |     |                 |








### PHOTOMETRIC DATA (MEASURED):



LED XB-H  
FWHM 50.0°  
Efficiency 80 %  
Peak intensity 0.9 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





LED XHP35 HD  
FWHM 52.0°  
Efficiency 78 %  
Peak intensity 1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED XHP35 HI  
FWHM 49.0°  
Efficiency 81 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




LED XHP50.2  
FWHM 47.0°  
Efficiency 86 %  
Peak intensity 1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





#### PHOTOMETRIC DATA (MEASURED):





LED XM-L  
FWHM 53.0°  
Efficiency 81 %  
Peak intensity 0.9 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





LED XM-L2  
FWHM 53.0°  
Efficiency 80 %  
Peak intensity 0.9 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED XP-E  
FWHM 51.0°  
Efficiency 81 %  
Peak intensity 1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





LED XP-E2  
FWHM 52.0°  
Efficiency 92 %  
Peak intensity 1.2 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





#### PHOTOMETRIC DATA (MEASURED):





LED XP-G  
FWHM 53.0°  
Efficiency 81 %  
Peak intensity 0.9 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





LED XT-E  
FWHM 46.0°  
Efficiency 80 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED H35C1 (LEMWA33)  
FWHM 52.0°  
Efficiency 81 %  
Peak intensity 1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





LED LUXEON 3030 2D (Round LES)  
FWHM 42.0°  
Efficiency 83 %  
Peak intensity 1.4 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





#### PHOTOMETRIC DATA (MEASURED):





LED LUXEON 3030 2D (Square LES)  
 FWHM 42.0°  
 Efficiency 83 %  
 Peak intensity 1.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





LED LUXEON 5050 Round LES  
 FWHM 41.0°  
 Efficiency 90 %  
 Peak intensity 1.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED LUXEON A  
 FWHM 50.0°  
 Efficiency 79 %  
 Peak intensity 1 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





LED LUXEON MZ  
 FWHM 41.0°  
 Efficiency 83 %  
 Peak intensity 1.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





### PHOTOMETRIC DATA (MEASURED):





LED LUXEON R  
FWHM 48.0°  
Efficiency 80 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





LED LUXEON Rebel ES  
FWHM 46.0°  
Efficiency 80 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED LUXEON T  
FWHM 49.0°  
Efficiency 82 %  
Peak intensity 1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





LED LUXEON TX  
FWHM 48.0°  
Efficiency 81 %  
Peak intensity 1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





#### PHOTOMETRIC DATA (MEASURED):





LED LUXEON V  
FWHM 46.0°  
Efficiency 79 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





LED LUXEON V2  
FWHM 47.0°  
Efficiency 88 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED NCSxx19B  
FWHM 45.0°  
Efficiency 80 %  
Peak intensity 1.2 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





LED NVSW219F  
FWHM 52.0°  
Efficiency 88 %  
Peak intensity 1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





#### PHOTOMETRIC DATA (MEASURED):





LED NVSW3x9A  
FWHM 48.0°  
Efficiency 78 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





LED NVSxx19B/NVSxx19C  
FWHM 46.0°  
Efficiency 81 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED NWSx229A  
FWHM 51.0°  
Efficiency 78 %  
Peak intensity 0.9 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





LED OSLOM Square EC  
FWHM 48.0°  
Efficiency 80 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



#### PHOTOMETRIC DATA (MEASURED):



**OSRAM**  
Opto Semiconductors

LED OSLON Square PC  
FWHM 48.0°  
Efficiency 79 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





**OSRAM**  
Opto Semiconductors

LED OSLON SSL 80  
FWHM 46.0°  
Efficiency 80 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





**SAMSUNG**

LED LH181A  
FWHM 34.0°  
Efficiency 87 %  
Peak intensity 1.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



**SAMSUNG**

LED LH181B  
FWHM 37.0°  
Efficiency 90 %  
Peak intensity 1.6 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




#### PHOTOMETRIC DATA (MEASURED):

|   |  |  |
|---|--|--|
| <p>SEOL<br/>SEOUL SEMICONDUCTOR</p> <p>LED Z5M3</p> <p>FWHM 46.0°</p> <p>Efficiency 88 %</p> <p>Peak intensity 1.1 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>   |  |  |
| <p>SEOL<br/>SEOUL SEMICONDUCTOR</p> <p>LED Z8Y22P</p> <p>FWHM 42.0°</p> <p>Efficiency 78 %</p> <p>Peak intensity 1.2 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p> |  |  |
| <p>SEOL<br/>SEOUL SEMICONDUCTOR</p> <p>LED Z8Y50P</p> <p>FWHM 42.0°</p> <p>Efficiency 77 %</p> <p>Peak intensity 1.2 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p> |  |  |


#### PHOTOMETRIC DATA (SIMULATED):




LED XP-G2 HE  
FWHM 62.0°  
Efficiency 97 %  
Peak intensity 0.8 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




LED LUXEON M/MX  
FWHM 45.0°  
Efficiency 94 %  
Peak intensity 1.4 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED NV4x144A  
FWHM 54.0°  
Efficiency 89 %  
Peak intensity 1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED OSCONIQ C 2424  
FWHM 32.0°  
Efficiency 94 %  
Peak intensity 2 cd/lm  
LEDs/each optic 4  
Light colour White  
Required components:




#### PHOTOMETRIC DATA (SIMULATED):

##### OSRAM

Opto Semiconductors


LED OSCONIQ P 3030  
FWHM 48.0°  
Efficiency 95 %  
Peak intensity 1.3 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



##### OSRAM

Opto Semiconductors


LED OSCONIQ P 7070  
FWHM 42.0°  
Efficiency 90 %  
Peak intensity 1.4 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



##### OSRAM


Opto Semiconductors

LED OSLOM Square CSSRM2/CSSRM3  
FWHM 50.0°  
Efficiency 90 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



SEOUL SEMICONDUCTOR

LED Z8Y22T  
FWHM 41.0°  
Efficiency 94 %  
Peak intensity 1.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salu, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)