



Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Product range	8501KA
Product type	Plug-in relay
Relay type	Alternating
Contact composition	NC - DPDT
[Uc] control circuit voltage	24 V AC/DC
Horsepower rating	0.33 Hp 120 V AC 0.5 hp 240 V AC
Mounting type	Socket
Pilot light	Green indicator on LED
Control type	Toggle switch

Complementary

Maximum switching voltage	240 V AC
Number of pins	11
Shape of pins	Tubular
For use with	8501NR61 8501NR62

Environment

Product certifications	UL recognized UL listed CSA RoHS CE
Height	1.73 in (44 mm)
Width	1.42 in (36 mm)
Depth	3.29 in (83.5 mm)

Ordering and shipping details

Category	21145 - 8501 KF,KL
Discount Schedule	CP2
GTIN	00785901919179
Package weight(Lbs)	0.11 kg (0.25 lb(US))
Returnability	No
Country of origin	CN

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes

China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
Contractual warranty	
Warranty	18 months