



**Characteristics:**

- Brushes minimize static charge generation and remove electrostatic charges to ground when held by grounded personnel
- Dissipative polypropylene black handles remove charges when grounded
- Available in 3 kinds of bristles - semi firm, firm, and soft
- Semi-firm and soft bristles are ideal for chemical and electronics applications
- Firm bristles are mainly for electronics, especially circuit boards
- Conductive handle's ESD properties are not effected by humidity as are wooden handle brushes
- Conductive copper based nylon bristles mixed with natural materials
- RTT Resistance:  $1 \times 10^3$  to  $<1 \times 10^5$  ohms tested per modified ANSI/ESD S4.1

**Materials:**

- Firm bristles - conductive yarn and hog hair\*
- Semi-firm bristles - conductive yarn and horse hair\*
- Soft bristles - conductive yarn and goat hair\*

\*Can contain additional natural fibers and animal hair has potential to shed



Item	Handle Type	Bristle Hardness	Overall Length	Overall Width	Bristle Length	Bristle Width	Bristle Height
<a href="#">35690</a>	Round	Firm	6" (152 mm)	5/16" (8 mm)	7/16" (11 mm)	3/16" (5 mm)	3/16" (5 mm)
<a href="#">35691</a>	Long	Firm	6" (152 mm)	1/2" (13 mm)	11/16" (17 mm)	1-1/4" (32 mm)	1/4" (6 mm)
<a href="#">35692</a>	Long	Firm	7" (178 mm)	1/2" (13 mm)	10/16" (16 mm)	2-3/8" (60 mm)	5/16" (8 mm)
<a href="#">35693</a>	Flat	Firm	6-1/4" (159 mm)	2-1/8" (54 mm)	3/4" (19 mm)	2" (51 mm)	3/16" (5 mm)
<a href="#">35694</a>	Flat	Semi-Firm	5-1/4" (133 mm)	5/16" (8 mm)	13/16" (21 mm)	1/2" (13 mm)	3/16" (5 mm)
<a href="#">35695</a>	Curved	Firm	4" (102 mm)	2-1/2" (64 mm)	1" (25 mm)	3" (76 mm)	1" (25 mm)
<a href="#">35696</a>	Flat	Firm	5-1/8" (130 mm)	5/16" (8 mm)	10/16" (16 mm)	1/2" (13 mm)	3/16" (5 mm)
<a href="#">36086</a>	Flat	Firm	5-3/4" (146 mm)	7/8" (22 mm)	3/4" (19 mm)	3/4" (19 mm)	3/16" (5 mm)
<a href="#">36087</a>	Flat	Firm	5-3/4" (146 mm)	1-1/16" (27 mm)	3/4" (19 mm)	7/8" (22 mm)	3/16" (5 mm)
<a href="#">36088</a>	Flat	Firm	6-1/4" (159 mm)	1-5/8" (41 mm)	3/4" (19 mm)	1-1/2" (38 mm)	3/16" (5 mm)
<a href="#">36098</a>	Round	Soft	6-5/16" (160 mm)	3/16" (5 mm)	1" (25 mm)	1/4" (6 mm)	1/4" (6 mm)

Designed to fulfill ANSI/ESD S20.20 requirement to ground all conductors at ESD workstation.

ESD Handbook TR20.20 Table 1 lists under Typical Static Electricity Sources "Brushes (camel/pig hair and synthetic bristles)."

"It should be understood that any object, item, material or person could be a source of static electricity in the work environment. Removal of unnecessary nonconductors, replacing nonconductive materials with dissipative or conductive materials and grounding all conductors are the principle methods of controlling static electricity in the workplace, regardless of the activity." (TR 20.20 section 2.4)

Unless otherwise noted, tolerance is  $\pm 10\%$ .

Specifications and procedures subject to change without notice.  
Made in Israel

Dimensions are taken from the bottom of the brush to the top of the bristles.

**Synthetic vs. Natural Bristles**

Synthetic bristles can easily become charged with static in standard humidity conditions. Natural hair usually builds static in areas of low humidity, but due to the conductive fibers in our brushes, this problem does not take effect. Generally speaking, once the conductive yarn is added to the bristles, it neutralizes the possibility of static build up caused by the natural hair.

**CONDUCTIVE BRUSHES**

3651 WALNUT AVE., CHINO, CA 91710  
PHONE: (909) 627-2453  
WEBSITE: [MendaPump.com](http://MendaPump.com)

**DRAWING NUMBER**  
35690

**DATE:**  
June  
2020

**MENDA**