



## Main

Range of product	9050JCK
Product or component type	Timer
Time delay type	Off-delay On-delay Interval One shot Repeat cycle On-delay and off-delay One shot falling edge Watchdog Trigger on-delay
Time delay range	0.05...9.99 s 0.1...99.9 s 1...999 h 1...999 min 1...999 s 0.1...99.9 h
[Uc] control circuit voltage	120 V AC

## Complementary

Hold-in power consumption in VA	3 VA
Line Rated Current	10 A
Switch function	DPDT
Contacts type and composition	2 NO + 2 NC
Contacts material	Silver nickel
Maximum switching voltage	240 V AC
Mounting support	Socket
Pin number	11
Shape of pin	Tubular
Product compatibility	8501NR61 8501NR62

## Environment

product certifications	CE RoHS UL listed UL recognized
ambient air temperature for operation	-18...150 °F
height	2.36 in (60 mm)
width	1.73 in (44 mm)
depth	3.58 in (91 mm)

## Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0703 - Schneider Electric declaration of conformity	Compliant - since 0703 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:

Nickel compounds, which is known to the State of California to cause cancer, and	Nickel compounds, which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>	For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>

Contractual warranty

Warranty period	18 months
-----------------	-----------