XGSZ22E4510



Main	
Range of product	OsiSense XG
Accessory / separate part category	Connection accessories
Accessory / separate part type	Connecting cable
Product or component type	Ethernet copper cable
Product compatibility	XGSZ33ETH XUW XGSZ33EIP
Accessory / separate part destination	Ethernet network

Complementary

Cable length	32.81 ft (10 m)	
Transmission rate	100 Mbit/s	
Transmission support medium	2 twisted shielded pairs	
Communication network category	5e	
AWG gauge	AWG 26	
Electrical connection	1 male connector, RJ45 straight connector with 4 pin(s) 1 male connector, M12 elbowed connector with 4 pin(s) - encoding type: D coding	
Conductor material	Copper	
Cover material	PUR	
Product weight	0.95 lb(US) (0.43 kg)	

Environment

IP degree of protection	IP67	
standards	EIA/TIA-568 IEC 60754-1 ISO/IEC 11801 Ed.2, 2002	
environmental characteristic	RoHS compliant	

Offer Sustainability

Not Green Premium product	Not Green Premium product
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the Stat of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and

Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm. harm.

For more information go to www.p65warnings.ca.gov For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period

18 months

Wiring Diagram

M12		Ĵ		RJ45
1	TD +		TD +	1
3	TD –	$+ \downarrow + \downarrow$	TD –	2
2	RD +	$H \rightarrow H$	RD +	3
4	RD –	ᡛᠠ╱᠊᠊ᢕ	RD –	6

