XGSZ22E4510



Main

Range of product	OsiSense XG	
Accessory / separate part category	Connection accessories	
Accessory / separate part type	Connecting cable	
Product or component type	Ethernet copper cable	
Product compatibility	XGSZ33ETH XUW XGSZ33EIP	
Accessory / separate part destination	Ethernet network	

Complementary

Cable length	32.81 ft (10 m)
Transmission rate	100 Mbit/s
Transmission support medium	2 twisted shielded pairs
Communication network category	5e
AWG gauge	AWG 26
Electrical connection	1 male connector, RJ45 straight connector with 4 pin(s) 1 male connector, M12 elbowed connector with 4 pin(s) - encoding type: D coding
Conductor material	Copper
Cover material	PUR
Product weight	0.95 lb(US) (0.43 kg)

Environment

IP degree of protection	IP67	. }
standards	EIA/TIA-568 IEC 60754-1 ISO/IEC 11801 Ed.2, 2002	9
environmental characteristic	RoHS compliant	

Offer Sustainability

Not Green Premium product	Not Green Premium product			
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:			
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and			
Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive harm. harm.				
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov			

Contractual warranty

Wiring Diagram

M12		戊			RJ45
1	TD+	H			1
3	TD-	⊬	-	TD-	2
2	RD+	H	-H	RD+	3
4	RD -	H	/ U	RD-	6