




Heyco® Original Strain Relief Bushings

Straight-Thru for Round Cables

.375" (9,5 mm) to .500" (12,7 mm) Mounting Holes

- **Protects the lifeline of your electric/electronic products** by absorbing the forces of pull, push, and twist that maybe exerted on the flexible power cord.
- Securely anchors, insulates, and protects cables at panel entry points.
- Sizes SR 2-Series to SR 6-Series for mounting hole diameters from .375" (9,5 mm) to .500" (12,7 mm).
- See page 4-38 for corresponding **Mounting Hole Plugs** which can be used to fill blank/unused Mounting Holes and thus allow for a single panel design for multiple applications.
- See pages 4-27 & 4-28 for SR assembly tools.
- **See schematic on page 4-20.**
- For Double D Mounting Hole Punches, see page 4-30.



WILL FIT THESE CABLES				PANEL DIMENSIONS						PART NO.	DESCRIPTION	PART DIM.		Mounting						
UL Type	AWG/ Conductors	Approximate Size		A Mounting Hole Dia.		B To Prevent Rotation		Finished Fit Panel Thickness*				Black	C BODY LENGTH		Hole Plug					
		in.	mm.	in.	mm.	in.	mm.	in.	mm.			in.	mm.	PART NO.						
AWM	12/1	.125- .187	3,2- 4,8	.375	9,5	.330	8,4	.062	1,6	1060	SR 2M-1	.406	10,3	2617						
SV & SVT	18/2	.220- .245	5,6- 6,2	.500	12,7	.450	11,4	.062	1,6	1157	SR 5MN-3	.438	11,1	2491						
Same as SR 5MN-3 above except								.100	2,5	1140	SR 5M-3	.438	11,1	2491						
For custom interlock cable, not UR		.250	6,4	.560	14,2	.730	18,5	.125	3,2	1487	SR 30-1A**	.672	17,1	consult Heyco						
		.265	6,7	.560	14,2	.730	18,5	.125	3,2	1490	SR 30-1B**									
SV & SVT	18/2	.250	6,4	.500	12,7	.450	11,4	.062	1,6	1150	SR 5N-4	.438	11,1	2491						
	18/3	.255	6,5	.500- .515	12,7- 13,1															
HPD	18/2	.270	6,9	.500	12,7	.450	11,4	.062	1,6	1150	SR 5N-4	.438	11,1	2491						
	16/2	.290	7,4	.500- .515	12,7- 13,1															
SJT	18/2	.300	7,6	.531	13,5	.450	11,4	.100 .156	2,5 4,0	1147 1154	SR 5P-4 SR 5L-1	.438 .438	11,1 11,1	2491						
Same as SR 5N-4 above except																				consult Heyco
SV & SVT	18/2 18/3	.255 .270	6,5 6,9	.500	12,7									.450	11,4	.100	2,5	1137	SR 5P3-4	.438
HPD	18/2	.290	7,4																	
SJ, SJT & SJO	18/2	.300	7,6	.500	12,7	.465	11,8	.090	2,3	1184	SR 6W-1	.438	11,1	2491						
SPT-3	16/2																			