

Adapter - HC-D-TA-M25-PLRBK - 1411352

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



EVO plastic adapter with bayonet locking, for EVO housing series D, for M25 screw connections.

Product Features



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	20.0 GRM
Custom tariff number	39269097
Country of origin	Poland

Technical data

Ambient conditions

Degree of protection	IP66 (DIN IEC 60529)
Ambient temperature (operation)	-40 °C ... 125 °C

General

Type of the screw connection	M25
Material	PA
Housing material	PA
Seal material	NBR
Thread type on connection side	Bayonet D plastic
Thread type on seal side	M25
Inflammability class according to UL 94	V2

Adapter - HC-D-TA-M25-PLRBK - 1411352

Classifications

eCl@ss

eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 8.0	27440202

ETIM

ETIM 4.0	EC000516
ETIM 5.0	EC000516

Approvals

Approvals

Approvals

EAC

Ex Approvals


Approvals submitted

Approval details

EAC

Drawings

Dimensional drawing



Dimensional drawing

