







REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN1770186	2017/07/13	Lingpeng	Modify The Pin Assignments Front View
C	CI90348	2019/03/06	Vicky	Change Note




Recommended Panel
Cut-Out



- Note:**
- * **QC** Important Dimension To Check.
 - * Waterproof Rate: IP67, Unmated.
 - * Housing: Thermoplastic, Black.
 - * Pin: Copper Alloy, Gold Plated.
 - * Nut: Thermoplastic, Black.
 - * Gasket: Rubber, Gray.
 - * Use with waterproof cap or dust cap
Maximum Panel Thickness: 2.3mm
 - * Use without waterproof cap or dust cap
Maximum Panel Thickness: 3.5mm
 - * Gasket and Nut are packed separately
in PE bags. (Gasket/Nut 不組裝, 散裝出貨)



Pin Assignments
Front View



UNIT:mm		TITLE MIDDLE PANEL SCREW 3PIN M CONN M PIN			ITEM NO ACC-03PMMS-SC7001		DRAWN BY Vicky		DATE 2019-03-06	
TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1°		SCALE 3:2	SIZE A4	SHEET 1 OF 1	DWG NO ACC-03PMMS-SC7001		CHECKED BY Rita		DATE 2019-03-06	
REV. C		WC-REV. A.2	QC : Inspection item		CUSTOMER ALTW		APPROVED BY Max		DATE 2019-03-06	

Amphenol LTW
安費諾亮泰企業股份有限公司