

**May not be suitable for all medical and aerospace applications.**

**Specifications: Contact Mallory Sonalert to discuss your application.**

|                                |                                                 |
|--------------------------------|-------------------------------------------------|
| Resonant Frequency (Hz)        | 2900 ± 500                                      |
| Operating Voltage Max (Vp-p)   | 30                                              |
| Rated Voltage (Vp-p)           | 5.0                                             |
| Current Consumption Max. (mA)  | 5.0 at Rated Voltage                            |
| Sound Pressure Level Min. (dB) | 95 at 10cm at Rated Voltage                     |
| Capacitance (pF)               | 30,000 ±30% @ 120Hz                             |
| Operating Temperature (°C)     | -20 ~ +90                                       |
| Storage Temperature (°C)       | -30 ~ +100                                      |
| Housing                        | ABS 777D UL94HB<br>plastic resin (Color: Black) |
| Leading Pin                    | Tin Plated Brass                                |
| Weight (Grams)                 | 12.6                                            |
| Condition by Wave (°C)         | 260 ± 5 / within 5 sec                          |
| Condition by Hand (°C)         | 350 ± 20 / within 5 sec                         |
| Options                        | For other options contact factory               |

**Dimensions:** (units: mm)

PS: Vp-p = 1/2duty, square wave

**RoHS Compliant**

