



Product: [88757](#)

Electronic, 4 Pr #22 Str TC, FEP Ins, FEP Jkt, CMP

[Request Sample](#)

Product Description

High Temperature Electronic, 4 Pair 22AWG (7x30) Tinned Copper, FEP Insulation, FEP Outer Jacket, CMP

Technical Specifications

Product Overview

Suitable Applications:	extreme high/low temperature environments; chemical resistant; outdoor and burial applications; low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; voice communications; panel wiring
------------------------	---

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
22	7x30	TC - Tinned Copper	4

Conductor Count:	8
------------------	---

Insulation

Material	Nominal Wall Thickness
FEP - Fluorinated Ethylene Propylene	0.0065 in

Color Chart

Number	Color
1	Black & Red
2	Black & White
3	Black & Green
4	Black & Blue

Outer Shield Material

Material
No Shield

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
FEP - Fluorinated Ethylene Propylene	0.2 in	0.009 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Conductor Loop DCR
16 Ohm/1000ft	32 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor
17 pF/ft

Inductance

Nominal Inductance

0.15 µH/ft

Impedance

Nominal Characteristic Impedance

88 Ohm

Current

Max. Recommended Current [A]

3.3 Amps per Conductor at 25°C (10°C Temperature Rise)

Voltage

UL Voltage Rating

300 V RMS

Temperature Range

Operating Temp Range: -70°C To +200°C

Mechanical Characteristics

Bulk Cable Weight: 28 lbs/1000ft

Max. Pull Tension: 62 lbs

Min Bend Radius/Minor Axis: 2 in

Standards

NEC Articles: Article 800

NEC/(UL) Compliance: CMP

CEC/C(UL) Compliance: CMP

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2003/96/EC (BFR): Yes

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2012/19/EU (WEEE): Yes

EU Directive 2015/863/EU: Yes

EU Directive Compliance: EU Directive 2003/11/EC (BFR)

EU CE Mark: Yes

EU RoHS Compliance Date (yyyy-mm-dd): 2005-04-01

MII Order #39 (China RoHS): Yes

Flammability, LSOH, Toxicity Testing

UL Flammability: NFPA 262

CSA Flammability: FT6

UL voltage rating: 300 V RMS

Plenum/Non-Plenum

Plenum (Y/N): Yes

Part Number

Non-Plenum Number: 8757

Variants

Item #	Color	Putup Type	Length	UPC
88757 0021000	Red	Reel	1,000 ft	612825217237

Footnote: C - CRATE REEL PUT-UP.

History

Update and Revision: Revision Number: 0.299 Revision Date: 06-08-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.