

Complementary N- and P-Channel 40-V (D-S) MOSFET

PRODUCT SUMMARY

	V _{DS} (V)	r _{DS(on)} (Ω)	I _D (A) ^a	Q _g (Typ)
N-Channel	40	0.030 at V _{GS} = 10 V	8	9.6
		0.034 at V _{GS} = 4.5 V	8	
P-Channel	- 40	0.032 at V _{GS} = - 10 V	- 8	21
		0.041 at V _{GS} = - 4.5 V	- 8	

FEATURES


- TrenchFET[®] Power MOSFET
- 100 % R_g and UIS Tested

APPLICATIONS

- CCFL Inverter
- LCD TV and Monitor




TO-252-4L
D-PAK



Top View
Drain Connected to
Tab

Ordering Information: SUD50NP04-62-T4-E3 (Lead (Pb)-free)



N-Channel MOSFET P-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS T_A = 25 °C, unless otherwise noted

Parameter		Symbol	N-Channel	P-Channel	Unit	
Drain-Source Voltage		V _{DS}	40	- 40	V	
Gate-Source Voltage		V _{GS}	± 16			
Continuous Drain Current (T _J = 150 °C)	T _C = 25 °C	I _D	8	- 8	A	
	T _C = 70 °C		8	- 8		
	T _A = 25 °C		8 ^{b, c}	- 8 ^{b, c}		
	T _A = 70 °C		8 ^{b, c}	- 8 ^{b, c}		
Pulsed Drain Current (10 μs Pulse Width)		I _{DM}	35	- 35		
Source-Drain Current Diode Current	T _C = 25 °C	I _S	8	- 8		
	T _A = 25 °C		5 ^{b, c}	- 5.5 ^{b, c}		
Pulsed Source-Drain Current		I _{SM}	35	- 35		
Single Pulse Avalanche Current	L = 0.1 mH	I _{AS}	10	20		
Single Pulse Avalanche Energy		E _{AS}	5	20	mJ	
Maximum Power Dissipation	T _C = 25 °C	P _D	15.6	23.5	W	
	T _C = 70 °C		10	15		
	T _A = 25 °C		6 ^{b, c}	6.7 ^{b, c}		
	T _A = 70 °C		3.9 ^{b, c}	4.3 ^{b, c}		
Operating Junction and Storage Temperature Range		T _J , T _{stg}	- 55 to 150		°C	

THERMAL RESISTANCE RATINGS

Parameter	Symbol	N-Channel		P-Channel		Unit
		Typ	Max	Typ	Max	
Maximum Junction-to-Ambient ^{b, d}	R _{thJA}	17	20.5	15.2	18.5	°C/W
Maximum Junction-to-Case (Drain)	R _{thJC}	6.6	8	4.4	5.3	

Notes:

a. Based on T_C = 25 °C.

b. Surface Mounted on 1" x 1" FR4 Board.

c. t = 10 sec.

d. Maximum under Steady State conditions is 53 °C/W (N-Channel) and 50 °C/W (P-Channel).

SPECIFICATIONS $T_J = 25\text{ }^{\circ}\text{C}$, unless otherwise noted

Parameter	Symbol	Test Conditions	Min	Typ ^a	Max	Unit		
Static								
Drain-Source Breakdown Voltage	V _{DS}	V _{GS} = 0 V, I _D = 250 μA	N-Ch	40		V		
		V _{GS} = 0 V, I _D = - 250 μA	P-Ch	- 40				
V _{DS} Temperature Coefficient	ΔV _{DS} /T _J	I _D = 250 μA	N-Ch		37			
		I _D = - 250 μA	P-Ch		- 38			
V _{GS(th)} Temperature Coefficient	ΔV _{GS(th)} /T _J	I _D = 250 μA	N-Ch		- 5			
		I _D = - 250 μA	P-Ch		4.0			
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	N-Ch	0.6			2.0	
		V _{DS} = V _{GS} , I _D = - 250 μA	P-Ch	- 0.8			- 2.2	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ± 16 V	N-Ch			100	nA	
			P-Ch			- 100		
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 40 V, V _{GS} = 0 V	N-Ch			1	μA	
		V _{DS} = - 40 V, V _{GS} = 0 V	P-Ch			- 1		
		V _{DS} = 40 V, V _{GS} = 0 V, T _J = 55 °C	N-Ch			10		
		V _{DS} = - 40 V, V _{GS} = 0 V, T _J = 55 °C	P-Ch			- 10		
On-State Drain Current ^b	I _{D(on)}	V _{DS} = 5 V, V _{GS} = 10 V	N-Ch	20			A	
		V _{DS} = - 5 V, V _{GS} = - 10 V	P-Ch	- 20				
Drain-Source On-State Resistance ^b	r _{DS(on)}	V _{GS} = 10 V, I _D = 6 A	N-Ch		0.025	0.030	Ω	
		V _{GS} = - 10 V, I _D = - 6 A	P-Ch		0.026	0.032		
		V _{GS} = 4.5 V, I _D = 4.8 A	N-Ch		0.028	0.034		
		V _{GS} = - 4.5 V, I _D = - 4.9 A	P-Ch		0.034	0.041		
Forward Transconductance ^b	g _{fs}	V _{DS} = 15 V, I _D = 6 A	N-Ch		20		S	
		V _{DS} = - 15 V, I _D = - 6 A	P-Ch		17			
Dynamic ^a								
Input Capacitance	C _{iss}	N-Channel V _{DS} = 20 V, V _{GS} = 0 V, f = 1 MHz	N-Ch		855		pF	
			P-Ch		1505			
Output Capacitance	C _{oss}	P-Channel V _{DS} = - 20 V, V _{GS} = 0 V, f = 1 MHz	N-Ch		105			
			P-Ch		230			
Reverse Transfer Capacitance	C _{rss}		N-Ch		65			
			P-Ch		175			
Total Gate Charge	Q _g	V _{DS} = 20 V, V _{GS} = 10 V, I _D = 5 A	N-Ch		21	32	nC	
		V _{DS} = - 20 V, V _{GS} = - 10 V, I _D = - 5 A	P-Ch		41	62		
	N-Channel V _{DS} = 20 V, V _{GS} = 4.5 V, I _D = 5 A	N-Ch		9.6	14.5			
		P-Ch		21	31			
Gate-Source Charge	Q _{gs}	P-Channel V _{DS} = - 20 V, V _{GS} = - 4.5 V, I _D = - 5 A	N-Ch		2.3			
	P-Ch			4.5				
Gate-Drain Charge	Q _{gd}		N-Ch		3.2			
			P-Ch		9.2			
Gate Resistance	R _g	f = 1 MHz	N-Ch		2.5	3.8	Ω	
			P-Ch		6.5	10		









SPECIFICATIONS $T_J = 25\text{ }^{\circ}\text{C}$, unless otherwise noted							
Parameter	Symbol	Test Conditions		Min	Typ ^a	Max	Unit
Dynamic ^a							
Turn-On Delay Time	$t_{d(on)}$	N-Channel $V_{DD} = 20\text{ V}$, $R_L = 4\text{ }\Omega$ $I_D \cong 5\text{ A}$, $V_{GEN} = 10\text{ V}$, $R_g = 1\text{ }\Omega$	N-Ch		6	12	ns
			P-Ch		7	14	
Rise Time	t_r		N-Ch		21	32	
			P-Ch		23	35	
Turn-Off Delay Time	$t_{d(off)}$	N-Ch		24	36		
		P-Ch		51	77		
Fall Time	t_f	N-Ch		9	15		
		P-Ch		50	80		
Turn-On Delay Time	$t_{d(on)}$	N-Channel $V_{DD} = 20\text{ V}$, $R_L = 4\text{ }\Omega$ $I_D \cong 5\text{ A}$, $V_{GEN} = 4.5\text{ V}$, $R_g = 1\text{ }\Omega$	N-Ch		12	20	ns
			P-Ch		40	60	
Rise Time	t_r		N-Ch		75	115	
			P-Ch		106	160	
Turn-Off Delay Time	$t_{d(off)}$	N-Ch		40	60		
		P-Ch		45	70		
Fall Time	t_f	N-Ch		56	85		
		P-Ch		50	75		
Drain-Source Body Diode Characteristics							
Continuous Source-Drain Diode Current	I_S	$T_C = 25\text{ }^{\circ}\text{C}$	N-Ch			8	A
			P-Ch			- 8	
Pulse Diode Forward Current ^a	I_{SM}		N-Ch			35	A
			P-Ch			- 35	
Body Diode Voltage	V_{SD}	$I_S = 1.5\text{ A}$	N-Ch		0.73	1.2	V
		$I_S = - 1.6\text{ A}$	P-Ch		- 0.73	- 1.2	
Body Diode Reverse Recovery Time	t_{rr}	N-Channel $I_F = 5\text{ A}$, $di/dt = 100\text{ A}/\mu\text{s}$, $T_J = 25\text{ }^{\circ}\text{C}$	N-Ch		26	40	ns
			P-Ch		30	45	
Body Diode Reverse Recovery Charge	Q_{rr}		N-Ch		21	32	nC
			P-Ch		24	36	
Reverse Recovery Fall Time	t_a	P-Channel $I_F = - 5\text{ A}$, $di/dt = - 100\text{ A}/\mu\text{s}$, $T_J = 25\text{ }^{\circ}\text{C}$	N-Ch		13		ns
			P-Ch		15		
Reverse Recovery Rise Time	t_b		N-Ch		13		
			P-Ch		15		

Notes:


a. Guaranteed by design, not subject to production testing.

b. Pulse test; pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.


Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless noted**Output Characteristics****Transfer Characteristics****On-Resistance vs. Drain Current****Capacitance****Gate Charge****On-Resistance vs. Junction Temperature**


N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless noted




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage




Threshold Voltage



Single Pulse Power, Junction-to-Ambient




Single Pulse Power, Junction-to-Case




* V_{GS} > minimum V_{GS} at which $r_{DS(on)}$ is specified

Safe Operating Area, Junction-to-Ambient


N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless noted




V_{DS} - Drain-to-Source Voltage (V)
* $V_{GS} >$ minimum V_{GS} at which $r_{DS(on)}$ is specified
Safe Operating Area, Junction-to-Case




Current Derating, Junction-to-Ambient



T_C - Case Temperature ($^{\circ}\text{C}$)
Current Derating, Junction-to-Case











Power Derating, Junction-to-Ambient









T_C - Case Temperature ($^{\circ}\text{C}$)
Power Derating, Junction-to-Case


*The power dissipation P_D is based on $T_{J(max)} = 150\text{ }^{\circ}\text{C}$, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless noted

Normalized Thermal Transient Impedance, Junction-to-Ambient

Normalized Thermal Transient Impedance, Junction-to-Case


P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless noted

P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless noted

Source-Drain Diode Forward Voltage

On-Resistance vs. Gate-to-Source Voltage

Threshold Voltage

Single Pulse Power, Junction-to-Ambient

Single Pulse Power, Junction-to-Case

Safe Operating Area, Junction-to-Ambient


P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless noted




* $V_{GS} >$ minimum V_{GS} at which $r_{DS(on)}$ is specified
Safe Operating Area, Junction-to-Case




Current Derating, Junction-to-Ambient



Current Derating, Junction-to-Case





Power Derating, Junction-to-Ambient



Power Derating, Junction-to-Case

*The power dissipation P_D is based on $T_{J(max)} = 150^\circ\text{C}$, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

**P-CHANNEL TYPICAL CHARACTERISTICS** 25 °C, unless noted**Normalized Thermal Transient Impedance, Junction-to-Ambient****Normalized Thermal Transient Impedance, Junction-to-Case**

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?74401>.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.