




- 1

USE WITH HAND TOOL: 220190-1
- 2

USE WITH AIR CORE DIELECTRIC ONLY
3. CENTER CONTACT CRIMP (HEX): 1.73 [.068]
4. SEE I.S. 9370

RECOMMENDED STRIP LENGTH

	OBSOLETE	RG-174/U, 174A/U, 188/U, 188A/U, 316/U	A	4.52 [.178]	58465-3	227194-1	—	9-413658-0	1-222246-0	222514-3	9-222506-1
	OBSOLETE	RG-58/U, 58A/U, 58B/U, 58C/U	A	5.41 [.213]	58465-1	—	—	9-221132-0	222246-2	222514-1	9-222506-0
	OBSOLETE	RG-223/U	A	5.41 [.213]	58465-1	—	—	8-221132-9	222246-2	222514-1	1-222506-1
	OBSOLETE	RG-188/316 TYPE DOUBLE BRAID	A	4.52 [.178]	58465-3	227194-1	—	9-413658-2	1-222246-0	222514-3	222506-9
	OBSOLETE	RG-141/U, 141A/U, BELDEN 9907, 89907	A	5.41 [.213]	58465-1	—	—	9-221132-0	1-222246-6	222514-1	222506-8
	OBSOLETE	RG-180/U, 180A/U, 180B/U, 195/U, 195A/U	A	4.52 [.178]	58465-3	—	—	9-413658-1	1-222246-3	222514-3	222506-7
	OBSOLETE	RG-179/U, 179A/U, 179B/U, 187/U, 187A/U	A	4.52 [.178]	58465-3	227194-1	—	9-413658-0	1-222246-3	222514-3	222506-6
		RG-174/U, 174A/U, 188/U, 188A/U, 316/U	A	4.52 [.178]	58465-3	227194-1	—	9-413658-0	1-222246-0	222514-3	222506-5
	OBSOLETE	RG-142/U, 142A/U, 412B/U, 400/U	A	5.41 [.213]	58465-1	—	—	9-221132-4	1-222246-6	222514-1	222506-4
SUPERSEDED BY 222506-1		RG-58/U, 58A/U, 58B/U, 58C/U	A	5.41 [.213]	58465-1	—	—	9-221132-0	222246-5	222514-1	222506-3
		RG-59/U, 59A/U, 59B/U, 62/U, 62A/U, 62B/U	B	6.48 [.255]	58465-1	—	227423-1	9-221132-1	222246-4	222514-2	222506-2
		RG-58/U, 58A/U, 58B/U, 58C/U	A	5.41 [.213]	58465-1	—	—	9-221132-0	222246-2	222514-1	222506-1
FOR USE WITH CABLE		VIEW	FERRULE CRIMP (HEX)	DIE SET 	 TUBING QTY=1	 SPACER QTY=1 	 FERRULE QTY=1	 CONTACT QTY=1	 PLUG ASSEMBLY QTY=1	PART NUMBER	