


1. MATERIALS AND FINISHES:
  - HD-BNC STR PLUG - BRASS, NICKEL PLATING
  - BNC STR PLUG - PHOSPHOR BRONZE, NICKEL PLATING
  - CABLE - BELDEN 4694R, BLACK
2. ELECTRICAL:
  - A. IMPEDANCE: 75 OHM
3. PACKAGING:
  - A. QUANTITY: SINGLE PACK
  - B. MARKING: BAG TO BE MARKED  
"AMPHENOL RF, 95-850-218-XXX AND DATE CODE"

REVISIONS

| REV | DESCRIPTION     | DATE      | ECO  | APPR |
|-----|-----------------|-----------|------|------|
| A   | RELEASE TO MFG. | 20-Nov-18 | 9701 | SK   |



| LENGTH TABLE              |                         |                                  |                                      |
|---------------------------|-------------------------|----------------------------------|--------------------------------------|
| PART NUMBER<br>(IMPERIAL) | PART NUMBER<br>(METRIC) | LENGTH IN INCHES<br>[METERS] 'L' | LENGTH 'X' IN INCHES<br>[METERS] MIN |
| 95-850-218-006            | -                       | 6.00 [0.152]                     | 0.75 [0.019]                         |
| -                         | 95-850-218M025          | 9.84 [0.250]                     |                                      |
| 95-850-218-012            | -                       | 12.00 [0.305]                    |                                      |
| 95-850-218-018            | -                       | 18.00 [0.457]                    |                                      |
| -                         | 95-850-218M050          | 19.69 [0.500]                    | 1.50 [0.038]                         |
| 95-850-218-024            | -                       | 24.00 [0.610]                    |                                      |
| -                         | 95-850-218M075          | 29.53 [0.750]                    |                                      |
| 95-850-218-036            | -                       | 36.00 [0.914]                    |                                      |
| -                         | 95-850-218M100          | 39.37 [1.000]                    |                                      |
| 95-850-218-048            | -                       | 48.00 [1.219]                    |                                      |
| -                         | 95-850-218M125          | 49.21 [1.250]                    |                                      |
| -                         | 95-850-218M150          | 59.06 [1.500]                    |                                      |
| 95-850-218-060            | -                       | 60.00 [1.524]                    |                                      |
| 95-850-218-072            | -                       | 72.00 [1.829]                    |                                      |
| -                         | 95-850-218M200          | 78.74 [2.000]                    |                                      |
| -                         | 95-850-218M300          | 118.11 [3.000]                   |                                      |
| 95-850-218-120            | -                       | 120.00 [3.048]                   |                                      |
| 95-850-218-144            | -                       | 144.00 [3.658]                   |                                      |
| 95-850-218-180            | -                       | 180.00 [4.572]                   |                                      |
| -                         | 95-850-218M500          | 196.85 [5.000]                   |                                      |
| 95-850-218-300            | -                       | 300.00 [7.620]                   |                                      |
| -                         | 95-850-218M10L          | 393.70 [10.000]                  |                                      |
| 95-850-218L050            | -                       | 600.00 [15.240]                  |                                      |
| -                         | 95-850-218M20L          | 787.40 [20.000]                  |                                      |
| 95-850-218L075            | -                       | 900.00 [22.860]                  |                                      |
| -                         | 95-850-218M30L          | 1181.10 [30.000]                 |                                      |
| 95-850-218L100            | -                       | 1200.00 [30.480]                 |                                      |

| TOLERANCE TABLE                 |                |
|---------------------------------|----------------|
| LENGTH IN INCHES/FT [METERS]    | TOLERANCE      |
| 0" - 23.90" [0 - 0.607]         | ±0.25" [0.006] |
| 24.00" - 59.00" [0.610 - 1.499] | ±0.50" [0.013] |
| 5.0' - 24.9' [1.524 - 7.617]    | ±2.5%          |
| 25.0' & UP [7.620 & UP]         | ±5.0%          |

|                                                            |                                                       |
|------------------------------------------------------------|-------------------------------------------------------|
| <input checked="" type="checkbox"/> FREQUENCY: DC - 12 GHz | <input checked="" type="checkbox"/> CONTINUITY        |
| <input type="checkbox"/> VSWR: ---- : 1 MAX                | <input checked="" type="checkbox"/> HI-POT : 300 VRMS |
| <input type="checkbox"/> INS. LOSS : ---- dB MAX           | <input type="checkbox"/> OTHER                        |

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:

|                  |                  |        |
|------------------|------------------|--------|
| 2 PLACE DECIMAL  | 3 PLACE DECIMAL  | ANGLES |
| ±.015 (0,381 mm) | ±.005 (0,127 mm) | ± 1°   |

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp., (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp., the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

|                              |                       |                   |                                                                                                  |  |                                       |                        |
|------------------------------|-----------------------|-------------------|--------------------------------------------------------------------------------------------------|--|---------------------------------------|------------------------|
| MATERIAL<br><br>SEE NOTES    | DRAWN<br>KAVI S       | DATE<br>25-Sep-18 | TITLE<br>75 OHM HD-BNC STR PLUG<br>TO BNC STR PLUG USING<br>BELDEN 4694R CABLE<br>VARIOUS LENGTH |  | Amphenol RF<br><br>www.amphenolrf.com |                        |
|                              | ENGINEER<br>KAVI S    | DATE<br>25-Sep-18 |                                                                                                  |  |                                       |                        |
| REFERENCE<br>EAR # 8638      | APPROVED<br>K.CAPOZZI | DATE<br>20-Nov-18 | SCALE: 1.5:1.0   SHEET 2 OF 2                                                                    |  | DRAWING NO.95-850-218-XXX             |                        |
| CONFIGURATION LEVEL: In Work | CAD FILE              |                   | DWG SIZE<br>B                                                                                    |  | REV<br>A                              | ITEM NO.95-850-218-XXX |
| FINISH                       |                       |                   |                                                                                                  |  |                                       | PART NO.95-850-218-XXX |