

FED. MFG. CODE 91929

CATALOG LISTING

15AS16

—FORD BRACKET P/N F3HT-9866-BA
MICRO SWITCH P/N 10-21615

✓FORD SWITCH P/N F1HT-9P775-AA
MICRO SWITCH CAT. LIST. YZ-3RL55517-W103

FORD CONNECTOR
P/N E43B-14A624-CA

1 - SEALED CONSTRUCTION PROVIDES SPLASH RESISTANCE
2 - FORD ASSEMBLY PART NUMBER "F3HT-9F857-BA" STAMPED
^ ON BRACKET

ON BRACKET
 3 TERMINAL CONNECTOR: PEC—PLASTICS ENG. DIV. — CONNECTOR P/N E43B-14A624-CA
 ALTAIR INTERNATIONAL — TERMINALS P/N E8EB-14461-HA
 STERLING PLASTICS — SPACER P/N EOAB-14A468-AA
 4 — LEADWIRE ORIENTATION: COMMON TERMINAL — BLACK WIRE
 NORMALLY OPEN TERMINAL — WHITE WIRE

ANSI Y14.5M-1982 APPLIES

ISSUE	M	CATALOG LISTING
	2	

15AS16

REVISIONS	
A	CO- 83499
WJC	
4	OCT 96

DDM/CAD
DRAWN

	CHECK	DCS	18 SEP 92	CHECK		RELEASE NO.	PR-20265	REPLACES
WJC	16 SEP 92	CHECK	DCS	18 SEP 92	CHECK			

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.


CHARACTERISTICS

OPERATING FORCE	— — — —	9 OZ MAX
RELEASE FORCE	— — — —	1/2 OZ MIN
DIFFERENTIAL TRAVEL	— — — —	.065 MAX
OVERTRAVEL	— — — — —	.060 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P N O

THIRD ANGLE PROJECTION



SCALE	FULL
-------	------

DO NOT SCALE PRINT

**UNLESS OTHERWISE SPECIFIED
TOLERANCES ARE**

ONE PLACE	(.0)	$\pm .030$
TWO PLACE	(.00)	$\pm .015$
THREE PLACE	(.000)	$\pm .005$

ANGLES	±
--------	---

WEIGHT .78 LBS MAX