# **ZCKE676**





#### Mair

Main	
Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJ1 ZCKJ11H29 ZCKJ11H7 ZCKJ1H29 ZCKJ1H7 ZCKJ2 ZCKJ2 ZCKJ21 ZCKJ21H29 ZCKJ2H47 ZCKJ2H29 ZCKJ2H7 ZCKJ4H7 ZCKJ4H29 ZCKJ4H7 ZCKJ4H7 ZCKJ4H29 ZCKJ4H7 ZCKJ4H7 ZCKJ4H29 ZCKJ4H7 ZCKJ4H29 ZCKJ4H7 ZCKJ5H29 ZCKJ5H7 ZCKJ5 ZCKJ5H7 ZCKJ6 ZCKJ6H29 ZCKJ6H7 ZCKJ6 ZCKJ6H29 ZCKJ7H7 ZCKJ7 ZCKJ7 ZCKJ7 ZCKJ7 ZCKJ7 ZCKJ7 ZCKJ7 ZCKJ8 ZCKJ8H7 ZCKJ8 ZCKJ8H7 ZCKJ8 ZCKJ8H7 ZCKJ8 ZCKJ8H7 ZCKJ8 ZCKJ8H7 ZCKJB3 ZCKJB11 ZCKJB31 ZCKJB31 ZCKJD31 ZCKJD35H7 ZCKJD35 ZCKJD35H7 ZCKJD37 ZCKJD37 ZCKJD37 ZCKJD37 ZCKJD37 ZCKJD37 ZCKJD39 ZCKJD39H7
Movement of operating head	Linear
Type of operator	Roller plunger spring return metal (reinforced)
T	Lataral annua als O dina ations

Lateral approach 2 directions

#### Complementary

Switch actuation	By 30° cam
Positive opening	With
Product weight	0.34 lb(US) (0.155 kg)
Head material	Metal

Type of approach

### **Environment**

ambient air temperature for operation	-40158 °F (-4070 °C)
ambient air temperature for storage	-40158 °F (-4070 °C)
environmental characteristic	Low temperature

## Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0951 - Schneider Electric declaration of conformity	Compliant - since 0951 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

### Contractual warranty

Warranty period	18 months

