# **XULK0830D**



#### Main

| Range of product              | OsiSense XU                              |
|-------------------------------|--|
| Series name                   | General purpose single mode              |
| Electronic sensor type        | Photo-electric sensor transmitter        |
| Sensor name                   | XUL                                      |
| Sensor design                 | Compact                                  |
| Detection system              | Thru beam                                |
| Material                      | Plastic                                  |
| Supply circuit type           | DC                                       |
| Wiring technique              | 2-wire                                   |
| Electrical connection         | 1 male connector M12, 4 pins             |
| Emission                      | Infrared thru beam                       |
| [Sn] nominal sensing distance | 26.25 ft (8 m) thru beam need a receiver |

# Complementary

| Enclosure material        | ABS  |     |
|---------------------------|--|-----|
| Lens material             | РММА                                       |     |
| [Us] rated supply voltage | 1224 V DC with reverse polarity protection |     |
| Supply voltage limits     | 1030 V DC                                  | _   |
| Current consumption       | <= 35 mA                                   |     |
| Delay first up            | <= 15 ms                                   | - 1 |
| Setting-up                | Without sensitivity adjustment             |     |
| Depth                     | 1.38 in (35 mm)                            |     |
| Height                    | 2.76 in (70 mm)                            | 1   |
| Width                     | 0.71 in (18 mm)                            |     |
| Product weight            | 0.3 lb(US) (0.135 kg)                      |     |
|                           |  |     |

## **Environment**

| product certifications                | CE   |  |
|---------------------------------------|--|--|
| ambient air temperature for operation | -13131 °F (-2555 °C)   |  |
| ambient air temperature for storage   | -40158 °F (-4070 °C)   |  |
| vibration resistance                  | 7 gn, amplitude = +/- 2 mm (f = 1055 Hz) conforming to IEC 60068-2-6 |  |
| shock resistance                      | 20 gn (duration = 11 ms) conforming to IEC 60068-2-27                |  |
| IP degree of protection               | IP671 conforming to NF C 20-010<br>IP67 conforming to IEC 60529      |  |

## Offer Sustainability

| Not Green Premium product  | Not Green Premium product   |  |
|--|---|--|
| Will be Compliant on 3Q2013  | Will be Compliant on 3Q2013 Will be Compliant on 3Q2013                                       |  |
| WARNING: This product can expose you to chemicals including:   | WARNING: This product can expose you to chemicals including:                                  |  |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and  | e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and |  |
| Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm. |   |  |
| For more information go to www.p65warnings.ca.gov  | For more information go to www.p65warnings.ca.gov   |  |

Contractual warranty



Warranty period

18 months

