



**SPECIFICATIONS: LINEAR POWER SUPPLY IHB120-0.2**

**MADE IN THE U.S.A.**

| <p><b>VAC INPUT:</b></p> <ul style="list-style-type: none"> <li>• 100/120/220/240 VAC, +10%, -13%</li> <li>• TOLERANCE FOR 230 VAC IS +15%, -10%</li> <li>• FREQUENCY RANGE: 47-63HZ</li> </ul> | <p><b>VAC JUMPERING AND FUSING REQUIREMENTS:</b><br/>SILKSCREENED ON CHASSIS FOR TRANSFORMER PRIMARY TERMINALS</p> <table border="1" data-bbox="857 919 1549 1010"> <thead> <tr> <th>For Use at</th> <th>115VAC</th> <th>230VAC</th> </tr> </thead> <tbody> <tr> <td>Jumper</td> <td>1&amp;3, 2&amp;4</td> <td>2&amp;3</td> </tr> <tr> <td>Apply AC</td> <td>1&amp;4</td> <td>1&amp;4</td> </tr> </tbody> </table> <p>MAX CURRENT/FUSE RATING      0.75A      0.375A</p> | For Use at | 115VAC | 230VAC | Jumper | 1&3, 2&4 | 2&3 | Apply AC | 1&4 | 1&4 |
|---|--|------------|--------|--------|--------|----------|-----|----------|-----|-----|
| For Use at  | 115VAC   | 230VAC     |        |        |        |          |     |          |     |     |
| Jumper  | 1&3, 2&4   | 2&3        |        |        |        |          |     |          |     |     |
| Apply AC  | 1&4  | 1&4        |        |        |        |          |     |          |     |     |
| <p><b>VDC OUTPUT:</b></p> <ul style="list-style-type: none"> <li>• ADJUSTABLE 100-135 VDC @ 0.2 AMP</li> </ul>  | <p><b>OVERVOLTAGE PROTECTION:</b></p> <ul style="list-style-type: none"> <li>• NOT PROVIDED. AVAILABLE BY ADDING AN IOVP12 MODULE</li> </ul> <p><b>SHORT CIRCUIT PROTECTION:</b></p> <ul style="list-style-type: none"> <li>• AUTOMATIC FOLDBACK</li> </ul> <p><b>OVERLOAD PROTECTION:</b></p> <ul style="list-style-type: none"> <li>• AUTOMATIC CURRENT LIMIT</li> </ul>   |            |        |        |        |          |     |          |     |     |
| <p><b>LINE REGULATION:</b></p> <ul style="list-style-type: none"> <li>• +/- 0.05% FOR A 10% LINE CHANGE</li> </ul>  | <p><b>LOAD REGULATION:</b></p> <ul style="list-style-type: none"> <li>• +/- 0.05% FOR A 50% LOAD CHANGE<br/>(DERATE OUTPUT CURRENT 10% FOR 50 HZ OPERATION)</li> </ul>   |            |        |        |        |          |     |          |     |     |
| <p><b>OUTPUT RIPPLE:</b> 5.0mV PK-PK MAXIMUM</p>  | <p><b>TRANSIENT RESPONSE:</b> &lt; 50 µsec per 50% LOAD CHANGE</p>   |            |        |        |        |          |     |          |     |     |
| <p><b>TEMPERATURE RATINGS:</b></p> <ul style="list-style-type: none"> <li>• OPERATING: 0°C TO 50°C FULL RATED<br/>DERATED LINEARLY TO 40% @ 70°C</li> <li>• STORAGE: -40°C TO +85°C</li> </ul>  | <p><b>TEMPERATURE COEFFICIENT:</b></p> <ul style="list-style-type: none"> <li>• TYPICAL: 0.01%/DEGREE C</li> <li>• MAXIMUM: 0.03%/DEGREE C</li> </ul>  |            |        |        |        |          |     |          |     |     |
| <p><b>STABILITY:</b> +/- 0.3% FOR 24 HOURS AFTER 1 HOUR WARM-UP</p>   | <p><b>EFFICIENCY (TYPICAL): 55%</b></p>  |            |        |        |        |          |     |          |     |     |
| <p><b>VIBRATION:</b></p> <ul style="list-style-type: none"> <li>• MIL-STD-810G, METHOD 514.6, CATEGORY 1, PROCEDURE1</li> <li>• RANDOM VIBRATION 10Hz - 2KHz, 6.15 grams (3 axis)</li> </ul>    | <p><b>SHOCK:</b></p> <ul style="list-style-type: none"> <li>• MIL-STD-810G, METHOD 516.6, PROCEDURE III</li> <li>• OPERATING: 20 GPK</li> </ul>  |            |        |        |        |          |     |          |     |     |
| <p><b>REMOTE SENSING:</b> NOT PROVIDED</p>  | <p><b>EMI/RFI:</b> INHERENT LOW CONDUCTED AND REDIATED NOISE LEVELS.</p> <ul style="list-style-type: none"> <li>• EMI: FCC CFR TITLE 47 PART 15 SUB-PART B</li> <li>• RFI: EN55022/CISPR22-LEVEL B COMPATIBILITY</li> </ul>  |            |        |        |        |          |     |          |     |     |

UL recognized for US and Canada – File#E133338/ CE Mark: LVD 92/59/EEC/ RoHs-5 Lead in Solder Exemption  
US and Canadian (Bi-National) standards: ANSI/UL 60950-1/-21; CAN/CSA C22.2 #60950-1/-21; IEC 60950-1

## CASE SIZE: B

