

Quad CMC Filters

16 Pin DIP and SMD Package



Product Features:

- Standard series of 16 pin quad CMC filters for Data Communications and Telecom applications.
- Operating Temp -40 to +85°C
- Hi Pot: 500Vrms
- Turns Ratio ($\pm 3\%$): 1:1
- UL Recognized Components

| Part Number | Package | OCL (μH typ.) | LL (μH max.) | Cw/w (pF max.) | DCR (Ω max.) | Impedance/Freq. Curve (typ.) | Temperature Range |
|---------------|---------|---------------------------|--------------------------|----------------|----------------------|------------------------------|-------------------|
| LD01-0756L1LF | DIP | 75 | 0.25 | 20 | 0.50 | A | 0 to +70°C |
| LD01-1006L1LF | DIP | 100 | 0.25 | 25 | 0.65 | B | 0 to +70°C |
| LG01-0356N2LF | SMD | 35 | 0.15 | 15 | 0.35 | C | 0 to +70°C |
| LG01-0956N2LF | SMD | 95 | 0.25 | 25 | 0.65 | D | -40 to +85°C |

Schematic



Impedance/Freq. Curve



Quad CMC Filters


DIP Package (L1)



SMD Package (N2)



Dimensions: inches [mm]
Co-Planarity: 0.004 [0.10]



Recommended
Solder Pad Dimensions

US Patent Numbers for SMD Package
5,656,985 6,297,721 B1
6,297,720 B1 6,320,489 B1
6,344,785 B1 6,662,431 B1



2880 Lakeside Drive #116
Santa Clara, CA 95054
(650) 903-3800
www.haloelectronics.com

HALO® Electronics is a leading supplier of high quality communication magnetics including signal transformers, filters, CMR chokes, PoE power transformers, DC/DC converters, and integrated Ethernet connectors. HALO's leading edge technology solutions are manufactured in ISO9001 and ISO14001 factories offering high quality products at a competitive price.