



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Interface**

According to IEC 61169-35  
Mechanically compatible with RPC-3.50 and SMA

**Documents**

Assembly instruction 02 A7

**Material and plating**

**Connector parts**

Center contact  
Outer contact  
Coupling nut  
Dielectric  
Gasket

**Material**

CuBe  
CuBe or equiv.  
Stainless steel  
PS  
Silicone

**Plating**

Gold, min. 0.8 µm, over chemical nickel  
Gold, min. 0.8 µm, over chemical nickel  
Passivated

RPC-2.92

Straight plug

**02S141-272E4**

**Electrical data**

Impedance	50 Ω
Frequency	DC to 40 GHz
Return loss	≥ 30 dB, DC to 4 GHz ≥ 22 dB, 4 GHz to 32 GHz ≥ 20 dB, 32 GHz to 40 GHz
Insertion loss	≤ 0.04 x √f(GHz) dB
Insulation resistance	≥ 5 GΩ
Test voltage (at sea level)	750 V rms
Working voltage (at sea level)	250 V rms
RF-leakage	≥ 100 dB up to 1 GHz

- Limitations are possible due to the used cable type -

**Mechanical data**

Mating cycles	≥ 500
Coupling test torque	1.70 Nm
Recommended torque	0.80 Nm to 1.10 Nm

**Environmental data**

Temperature range	-40°C to +85°C
Thermal shock	MIL-STD-202, Method 107, Condition B
Corrosion	MIL-STD-202, Method 101, Condition B
Vibration	MIL-STD-202, Method 204, Condition D
Shock	MIL-STD-202, Method 213, Condition I
Moisture resistance	MIL-STD-202, Method 106
RoHS	compliant

**Tooling**

N/A

**Suitable cables**

UT-141, RTK-Flex 402, UT-141-A-TP

**Weight**

2.6 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
A. Maiwälder	30.07.08	F. Reiner	26.06.18	b01	18-1026	M. Ruf	25.06.18