

Optical element - PSD-S OE LED BL CL - 2700128

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



LED blinking light element, 24 V AC/DC, clear

Product Features

- High light and color intensity
- Can be freely combined
- Minimum LED service life of 50,000 h
- ☑ IP65 protection

Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	60.0 GRM
Custom tariff number	85318095
Country of origin	Germany

Technical data

Dimensions

Diameter	70 mm
Height	65.5 mm

Ambient conditions

Ambient temperature (operation)	-20 °C 50 °C
Degree of protection	IP65, when installed or with cover

General

Material	Polycarbonate PC
Calotte color	clear
Weight	59 g
Mounting position	any



Optical element - PSD-S OE LED BL CL - 2700128

Technical data

General

Rubber seal pre-installed for each element
24 V AC/DC
max. 500 mA
25 mA
max. 100,000 h
100 %
LED flashlight
approx. 1 Hz

Approvals / conformities

Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
-------------------------------	--

Classifications

eCl@ss

eCl@ss 4.0	27143203
eCl@ss 4.1	27143203
eCl@ss 5.0	27371220
eCl@ss 5.1	27371220
eCl@ss 6.0	27371220
eCl@ss 7.0	27371220
eCl@ss 8.0	27371220

ETIM

ETIM 3.0	EC000232
ETIM 4.0	EC000232
ETIM 5.0	EC000232

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	39121311
UNSPSC 12.01	39121311
UNSPSC 13.2	39121311

Approvals

Approvals



Optical element - PSD-S OE LED BL CL - 2700128

Approvals
Approvals
UL Listed / cUL Listed / cULus Listed
Ex Approvals
Approvals submitted
Approval details
UL Listed (I)
cUL Listed • • • • • • • • • • • • • • • • • • •
cULus Listed ()

Phoenix Contact 2014 © - all rights reserved http://www.phoenixcontact.com