

TECHNICAL CHARACTERISTICS

MATERIAL
COLOR: BLACK
STYLE: UL1007

ENVIRONMENTAL
OPERATING TEMPERATURE: -20°C UP TO 80°C
COMPLIANCE: LEAD FREE AND ROHS

WIRE DIMENSION
AWG: 26


PACKAGING
10 PCS/BAG

A

B

C

D



Terminal A	662 005 137 22
Terminal B	662 005 137 22

RoHS Compliant				PROJECTION: 	GENERAL TOLERANCE .X = $\pm$/_ 0.2 .XX = $\pm$/_ 0.15			
G								
F								
E								
D								
C				APPROVAL: BBu	UNIT: MM	DESCRIPTION: WR-MPC3 3.00 MM MALE PRE-CRIMPED CABLE		SIZE A4
B					SCALE:			
A	24-NOV-15	PDF	AK		SHEET: 1/2	WERI PART NO: 662 562 526 030		
REV	DATE	FILE	BY		DRAW: AK			

1				2				3				4				5				
Cautions and Warnings: This electronic component is designed and developed with the intention for use in general electronics equipments. Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Würth Elektronik must be asked for a written approval. In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.																	A			
																	B			
																	C			
																	D			
RoHS Compliant																				
G				PROJECTION: 				GENERAL TOLERANCE .X = +/- 0.2 .XX = +/- 0.15												
F																				
E																				
D																				
C				APPROVAL: JC				UNIT: MM				DESCRIPTION: DISCLAIMER				SIZE				
B								SCALE:				WERI PART NO: DISCLAIMER				A4				
A	10-SEP-14	PDF	QL					SHEET: 2/2												
REV	DATE	FILE	BY					DRAW: QL												