




STRAIGHT BULKHEAD JACK PANEL SEAL
REAR MOUNT CRIMP TYPE - CABLE 2.6/50 S
R143.331.161

Series : TNC-COM


PANEL CUT OUT

A	mm		C	mm	
	Maxi	mini		Maxi	mini
B	12.8	12.7	D	12.8	12.7
	12.1	12		10.9	10.8

All dimensions are in mm.



COMPONENTS	MATERIALS	PLATING
BODY	BRASS	NICKEL 2 μm
CENTRE CONTACT	BERYLLIUM COPPER	GOLD 0.2 OVER NICKEL 2 μm
OUTER CONTACT	-	- μm
INSULATOR	PTFE	
GASKET	SILICONE RUBBER	
OTHERS PARTS	BRASS	NICKEL 2 μm
-	-	-
-	-	-



Edition : 9845 B

Design changes may be in order to improve the product.

STRAIGHT BULKHEAD JACK PANEL SEAL**R143.331.161****REAR MOUNT CRIMP TYPE - CABLE 2.6/50 S****Series : TNC-COM****ELECTRICAL CHARACTERISTICS**

Impedance	50 Ω
Frequency	0-1.5 GHz
VSWR	NA + 0.000 x F(GHz) Maxi
Insertion loss	NA √F(GHz) dB
RF leakage	- (NA - F(GHz)) dB mini
Operating temperature	-35/+70 °C
Voltage rating	335 Veff Maxi
Dielectric withstanding	1000 Veff mini
Insulation resistance	5000 MΩ mini

SPECIFICATION

Stripping	a	b	c	d	e	f
mm	4.00	10.0	18.5	0.00	14.5	0.00

Assembly instruction : **Crimp 03**

Recommended cables

RG 316

RG 188

KX 22A

Cable retention

- pull off **40** N mini- torque **NA** N.cm**MECHANICAL CHARACTERISTICS**

Centre contact retention	
Axial force – Mating end	10 N mini
Axial force – Opposite end	10 N mini
Torque	NA N.cm mini

Recommended torque

Mating **NA** N.cmPanel nut **370** N.cmClamp nut **NA** N.cmA/F clamp nut **0.000** mmMating life **100** Cycles miniWeight **0.000** g**TOOLING**

Part Number	Description	Hexagon
.	.	.
R282.235.011	CRIMPING DIES	1.73-5.41
R282.293.000	CRIMPING TOOL	-
R282.223.000	CRIMPING TOOL	1.73-5.41

OTHERS CHARACTERISTICS

-

ENVIRONMENTAL

Hermetic seal	NA Atm.cm3/s
Leakage – pressurised only	NA Mpa

**Edition : 9845 B**

Design changes may be in order to improve the product.